



No Hassle Compression

CC40 – 40 HP

DISCHARGE PRESSURE (psig)

		60	80	100	120	140	160	180	200	220	240	250
SUCTION	5	330	330	294	290	286	250	216	210	195	188	184
	10	420	420	325	325	320	275	270	242	218	210	210
	20		540	470	450	355	352	350	295	280	250	250
	30		610	610	545	470	400	320	315	310	290	285
	40			590	590	500	490	400	400	400	365	350
	50				695	600	585	480	475	400	400	375
	60					700	700	550	550	460	455	450
	70						795	650	645	530	525	520

Pressures in PSIG Flow Rates in MSCFD
 Performance based on 2500 ft, gas density .665, ambient temp 68°F
 using Enduro G-2 V2 Selector Program

CC40

Standard Features

- Compressor – Gardner Denver Enduro 12
- Driver – GM 3000
- Weight – 4,800 lb/2,200 kg
- Compressor Speed Optimization

Options

- CPC Controller
- Sound Proofing
- Metering
- SCADA Output
- Blowcase
- Fire & Gas Detection



Phone: (403) 219-3026
 Fax: (403) 717-1759

#8, 1820 – 30th Ave NE
 Calgary, Alberta Canada T2E 7M5

info@compactcompression.com