

FOR: ELL/ Winter Petroleum

AREA: Rainbow Lake

LSD: 10-24-110-04W6M

ENGINE CATERPILLAR G3306TA S/N: G 6X01555
Ignition: Mag: Altronic III 6A29H-A0 Coils: Altronic P/N: 591011B
Plugs: Champion RTN79G Power Source: N/A
Starter: TDI, Std T306-60015-02R
Oil Filter: Cat P/N IR0716
Air Filter: 6N6444 (Inner) 7W5313 (Outer) Fuel Filter: Parker 200-35-DX Element
CRN# : OE 7415.5

COOLER AIR-X-CHANGERS 72AVI
Fan: Moore 72", 4 Blade, Left Hand, CL5K Pitch: 6.4° Angle at Clevis
Shaft Bearings: Main: 2-3/16" Dodge S2000 Idler: 2-3/16 Dodge FB/CC203
Drive Belts: BX-120 (2) Louvre Actuator: Garzo 501-12
Coolant Hoses: Engine In: NAPA 7231 2" straight Engine Out: NAPA 7197 1-3/4" 90°
AW Sect. S/N: 055580 JW Sect. S/N: 055580
IC Sect. S/N: 055580.3 MAWP: 1292 AC Sect S/N: 055580.4 MAWP: 1292
CRN# : R8395.213 CRN# R7796.213

PROCESS Filter Coalescer: 16" " Dia S/N: 050625-01 MAWP: 707 Psig
CRN# : P 8055.213 @ 545079

Elements: () PECO FG-36-MS
Relief Valves: LHS (Cyl #A2) Farris 'D' set @ 207 Psig
RHS (Cyl #2) Farris 'C' set @ 1292 Psig

Orifices: Refer to the Process Flow Sheet in the Drawing Section of your Operating Manual.

* Auto Bypass: Model: Fisher D-4 Orifice: 1/2" Action: F/O

Compressor Unit Inlet System: Refer to Process Flow Sheet in the Drawing section of your Operating Manual.

Checked By:



PANEL Process Pressure Gauge Ranges

CYL #1 suction : 0 - 300 Psig
CYL #1 discharge : 0 - 1000 Psig
CYL #2 discharge : 0 - 1500 Psig

Note: Process Pressure and Temperature Shutdown Settings should be reset to reflect actual operating field conditions.

FLUIDS Oil: Petro Canada Sentinal 445 Engine Capacity: 151 litres (33.5 Imp gal)
Comp. Capacity: 15 litres (3.3 Imp gal)
Engine Coolant: UCARTHERM 50/50 Capacity: 130 litres (29 Imp gal)

COMPRESSOR

ARIEL JGA/2 Frame S/N: F 21555
Oil Filter: Ariel P/N: A-0661

CONFIGURATION	THROW #2	THROW #1
Cylinder #	A2	A1
Stage #	1	2
Cylinder Bore, In.	4 3/4"	3"
Class	JG	JG
MAWP, Psig	865	2550
Cylinder S/N	C-71172	C- 65737

CLEARANCE FEATURES

High Clearance Assy., Qty:	N/R	N/R
VVCP, S/N (or NA):	U-43989	U-40333

VALVES

Suction: Part # (as shipped)	B-3395-S	B-2930-CC
Discharge: Part # (as shipped)	B-3396-DD	B-2929-P

Valve Operating Ranges: Refer to the Performance Section in your Operating Manual.

BALANCE AND LUBRICATION: Refer to the Frame section in your Operating Manual.

COUPLING

Type: 350CMR

ELECTRICAL CSA Reg#:

* Denotes Options

Checked by:

