



1. WEIGHT OF SKID STEEL BASE: 2275 KGS
2. WEIGHT OF COMPRESSOR/MOTOR BASE: 135 KGS
3. TOTAL WEIGHT: 2410 KGS
4. COPE FLANGES WHERE REQUIRED.
5. ALL CUT FLANGES TO BE 1/4" FILLETS ALL AROUND, UNLESS OTHERWISE NOTED.
6. ALL CUT LENGTHS ARE EXACT TO +0.0"/-0.125" (+0 MM/-3 MM)
7. ALL BOLT HOLES ARE 3/4"Ø(19 MM) UNLESS OTHERWISE NOTED.
8. SURFACE PREP: SANDBLAST TO SSPC-SP6
9. PRIMER: ONE COAT OF RED OXIDE PRIMER
10. PAINT: ONE COAT OF PLATINUM GREY ENAMEL
11. FULL PENETRATION STRENGTH WELD IS REQ'D AT THESE LOCATIONS.
12. PERMETER AND ALL PANEL JOINTS OF CHECKER PLATE ARE TO BE SEAL WELDED. SKID MEMBERS TO UNDERSIDE OF CHECKER PLATE TO BE STITCH WELDED AT 27(50 MM) OF FILLET ON 16(405 MM) CENTERS.
13. ALL TAIL DIMENSIONS FROM REFERENCE POINT.

CHECKER PLATE DETAIL

TITLE: STRUCTURAL STEEL	FOR:
----------------------------	------

			
TITLE:		STRUCTURAL STEEL	
FOR:		ROZSA PETROLEUM LTD. ROZSA ENHANT BATTERY 100 HP BOOSTER UNIT LSD: 10-20-12-60-W4M	
DRWING BY:	DATE:	CHKD. BY:	SCALE:
G. STANINESS	JUN. 6, 1988	D. JAMES	1 : 15
APPR. BY:	W.D. No:		
D. JAMES	10309301		
CUST. PO. No:	DRWG. No:	SHEET No:	REV:
	10309-301	1 OF 2	3