Canadian N	latural		PRESSUR VISUAL IN REPORT	E VESSEL SPECTION		eport #: ct Date: Page: . Job #:		<b>5741-MD-29</b> )2/17/2012 1 of 11 155741
Criticality Designation:			Yell	ow				
Insp. Comp: <u>Matrix_Insp</u> Location: <u>12-29-096</u> Jurisdiction #: <u>A30909</u> CRN #: <u>M8242</u>	Dection -11W6 Uni 903 Equ	it / Skid #:	Grande Prairie - 7714 V-2201 N/A	North	LS	D:1 #:	2-29-0 95 (	Hamburg 196-11W6 016 D 995
Manufacturer: DON BUCK FA	BRICATION CO		quipment Descripti		OPANE ACC			
Status: In Service - MAWP Shell: 1874 kPa MAWP Tube: MDMT: -28 °C Support Saddle C.A.: 0.063 in.	@ RT: <u>RT-2</u>	C Hei Size	ip. Type: <u>Vessel: /</u> Volume: ght/Length: <u>1</u> /Diameter.: <u>48</u> inal CNRL Inventor Clad: No	2 Ft. in. O.D.	⊠ N	Code St Insul P\ Mar	tamp: lated: WHT: nway:	Y N
Component	Mater		Nominal Th		1	1		Shell Side
1 Main - Shell	SA-516		0.500 in.	48.000 in			]	$\boxtimes$
2 West - Head	SA-516		0.480 in.	48.000 in			]	
3 East - Head	SA-516	6-70	0.480 in.	48.000 in	. OD			
4 - 5 -							]	
Static Data: Confirmed	Changed (See C	Comments	) 🖂					
Static data updated								
Static data updated		Serial #:	VA0090043 01		CRN: _(	02176.52	2	
Static data updated SV Static Data PSV –1 Tag #: 78 Model #: JBS 15J			VA0090043 01 4407 SCFM		Pressure: 2	271.8 ps		
Static data updated SV Static Data PSV –1 Tag #: 78 Model #: JBS 15J Manufacturer: Crosby			-	Service	Pressure: 2 Company: 1	271.8 ps Гусо	si	
Static data updated SV Static Data PSV –1 Tag #: 78 Model #: JBS 15J Manufacturer: Crosby Inlet Size & Type: 3.00 i	in Flanged		-	Service Last Ser	Pressure: 2 Company: 1 vice Date: 0	271.8 ps Гусо )6/12/200	si 07	
Static data updated SV Static Data PSV –1 Tag #: 78 Model #: JBS 15J Manufacturer: Crosby	in Flanged		-	Service Last Ser Block Valve:	Pressure: 2 Company: 1 vice Date: 0	271.8 ps Гусо 06/12/200 Carseale	si 07	pen
Static data updated SV Static Data PSV –1 Tag #: 78 Model #: JBS 15J Manufacturer: Crosby Inlet Size & Type: 3.00 i Outlet Size & Type: 6.00 i	in Flanged in Flanged	Capacity:	-	Service ( Last Ser Block Valve: Co	Pressure: 2 Company: 1 vice Date: 0 Upstream -	271.8 ps Гусо 06/12/200 Carseale Yes	si 07 ed - Op	pen
Static data updated SV Static Data PSV –1 Tag #: 78 Model #: JBS 15J Manufacturer: Crosby Inlet Size & Type: 3.00 i Outlet Size & Type: 6.00 i Carseal Intact: Yes Shell Side / Tube Side: S	in Flanged in Flanged	Capacity:	4407 SCFM	Service ( Last Ser Block Valve: Co	Pressure: 2 Company: 1 vice Date: ( Upstream - ( de Stamp: ) on of PSV: (	271.8 ps Fyco D6/12/200 Carseale Yes Dn Vesse	si 07 ed - Op el	pen
Static data updated SV Static Data PSV –1 Tag #: 78 Model #: JBS 15J Manufacturer: Crosby Inlet Size & Type: 3.00 i Outlet Size & Type: 4.00 i Carseal Intact: Yes	in Flanged in Flanged hell Side	Capacity: Out for S Serial #:	4407 SCFM	Service ( Last Ser Block Valve: Co .: <u>N</u> Locatio	Pressure: 2 Company: 1 vice Date: ( Upstream - ( de Stamp: ) on of PSV: (	271.8 ps Гусо 06/12/200 Carseale Yes On Vesse 0G201.2	si 07 ed - Op el	ben
Static data updated SV Static Data PSV –1 Tag #: 78 Model #: JBS 15J Manufacturer: Crosby Inlet Size & Type: 3.00 i Carseal Intact: Yes Shell Side / Tube Side: S PSV –2 Tag #: 179 Model #: 951111MA Manufacturer: Crosby	in Flanged in Flanged hell Side	Capacity: Out for S Serial #:	4407 SCFM Service During Insp VA 0090390 01	Service ( Last Ser Block Valve: Co Co : <u>N</u> Locatic Set Service (	Pressure: 2 Company: 1 vice Date: 0 Upstream - 0 de Stamp: 1 On of PSV: 0 CRN: 0 Pressure: 2 Company: 1	271.8 ps Fyco D6/12/200 Carseale Yes Dn Vesse DG201.2 284 psi Fyco	si 07 ed - Op el	pen
Static data updated   SV Static Data   PSV –1 Tag #: 78   Model #: JBS 15J   Manufacturer: Crosby   Inlet Size & Type: 3.00 i   Outlet Size & Type: 6.00 i   Carseal Intact: Yes   Shell Side / Tube Side: S   PSV –2 Tag #: 179   Model #: 951111MA   Manufacturer: Crosby   Inlet Size & Type: 0.75 i	in Flanged in Flanged hell Side	Capacity: Out for S Serial #:	4407 SCFM Service During Insp VA 0090390 01	Service ( Last Ser Block Valve: Co Co : N Location Service ( Last Ser	Pressure: 2 Company: 1 vice Date: ( Upstream - ( de Stamp: ) on of PSV: ( Pressure: 2 Company: 1 vice Date: (	271.8 ps Fyco D6/12/200 Carseale Yes Dn Vesse DG201.2 284 psi Fyco D6/14/07	si 07 ed - Op el	
Static data updated   Static Data   PSV –1 Tag #: 78   Model #: JBS 15J   Manufacturer: Crosby   Inlet Size & Type: 3.00 i   Outlet Size & Type: 6.00 i   Carseal Intact: Yes   Shell Side / Tube Side: S   PSV –2 Tag #: 179   Model #: 951111MA   Manufacturer: Crosby   Inlet Size & Type: 0.75 i   Outlet Size & Type: 1.00 i	in Flanged in Flanged hell Side	Capacity: Out for S Serial #:	4407 SCFM Service During Insp VA 0090390 01	Service ( Last Ser Block Valve: Co : N Location : N Service ( Last Ser Block Valve:	Pressure: 2 Company: 1 vice Date: ( Upstream - ( de Stamp: ) on of PSV: ( Pressure: 2 Company: 1 vice Date: ( Upstream - (	271.8 ps Fyco 06/12/200 Carseale Yes Dn Vesse 06201.2 284 psi Fyco 06/14/07 Carseale	si 07 ed - Op el	
Static data updated   SV Static Data   PSV –1 Tag #: 78   Model #: JBS 15J   Manufacturer: Crosby   Inlet Size & Type: 3.00 i   Outlet Size & Type: 6.00 i   Carseal Intact: Yes   Shell Side / Tube Side: S   PSV –2 Tag #: 179   Model #: 951111MA   Manufacturer: Crosby   Inlet Size & Type: 0.75 i   Outlet Size & Type: 1.00 i   Carseal Intact: Yes	in Flanged in Flanged hell Side n Threaded in Threaded	Capacity: Out for S Serial #: Capacity:	4407 SCFM Service During Insp VA 0090390 01 434 SCFM	Service ( Last Ser Block Valve: Co : N Locatio : Service ( Last Ser Block Valve: Co	Pressure: 2 Company: 1 vice Date: ( Upstream - ( de Stamp: ) on of PSV: ( Pressure: 2 Company: 1 vice Date: ( Upstream - ( de Stamp: )	271.8 ps Fyco D6/12/200 Carseale Yes Dn Vesse DG201.2 284 psi Fyco D6/14/07 Carseale Yes	si 07 ed - Op el ed - Op	
Model #:JBS 15JManufacturer:CrosbyInlet Size & Type:3.00 iOutlet Size & Type:6.00 iCarseal Intact:YesShell Side / Tube Side:SPSV -2 Tag #:179Model #:951111MAManufacturer:CrosbyInlet Size & Type:0.75 iOutlet Size & Type:1.00 i	in Flanged in Flanged hell Side n Threaded in Threaded	Capacity: Out for S Serial #: Capacity:	4407 SCFM Service During Insp VA 0090390 01	Service ( Last Ser Block Valve: Co : N Locatio : Service ( Last Ser Block Valve: Co	Pressure: 2 Company: 1 vice Date: ( Upstream - ( de Stamp: ) on of PSV: ( Pressure: 2 Company: 1 vice Date: ( Upstream - (	271.8 ps Fyco D6/12/200 Carseale Yes Dn Vesse DG201.2 284 psi Fyco D6/14/07 Carseale Yes	si 07 ed - Op el ed - Op	



#### PRESSURE VESSEL VISUAL INSPECTION REPORT

**155741-MD-29** 02/17/2012 2 of 11

155741

Insp. Company: Ma	trix_Ir	nspection	LSD:	12-29-096-11W6	Jurisdiction #:	Jurisdiction #: A3090	
External Inspection Results	– VE	External In	spection Per	formed			
Item	N/A	Condition	(C	Comment Check Status Bar or Press F1 for Help)	NCR	Action Item Integrity	Action Item Maintenance
Nameplate		Accept	Firmly affixe	ed and legible			
Foundation and Supports		Accept	Large skid o	on pilings outside Unit# 7714			
Anchor Bolts		Accept	Secure & tig	ght with minor corrosion			
Grounding		Accept	Grounded d	lirectly to accumulator saddle			
Insulation Condition	$\boxtimes$		No insulatio	n			
PSV		Reject	Due for serv	vice			$\boxtimes$
Shell Heads & Nozzles		Accept	No recordat	ole mechanical damage			
Metal Surfaces (Paint)		Accept	Staining and	d minor surface corrosion			$\boxtimes$
Aux Equipment	$\boxtimes$		No auxiliary	equipment			
Cathodic Protection	$\boxtimes$		No external	anode			
Alignment		Accept	Acceptable	condition			
Flange Connections		Accept	Minor corro	sion noted between the flanges			
Pressure Gauge		Accept	0-2100 kPa	/ 0-300 psi: acceptable range			
Temperature Gauge	$\boxtimes$		No tempera	ture gauge			
Sight Glass		Accept	clear and in	tact			
Ladder / Platform	$\boxtimes$		No ladder o	r platform			
Leaks		No	No evidence	e of leaks			
Piping from Vessel		Accept	Adequately	supported from flange to flange	L.		
Previous UT Survey		No	Not previou	sly marked & no history	UT Compan	y: N/A	

#### **External Visual Observations**

The accumulator has minor stains noted throughout with minor chipped coating exposing the base metal to minor suface corrosion with no pitting noted at the time of inspection.

There is minor surface corrosion build-up noted between the flanged connections.

The PSV is due for service. The inlet flange to the PSV is taped which may accelerate corrosion between the flanges due to entrapped moisture.

PSV #2 is on its side.

A UT corrosion survey was performed with no significant metal loss recorded at the time of inspection.

Recommendations:

Service the PSVs and ensure PSV #2 is installed in an upright position

Remove the tape from the flanges

Clean and touch-up the coating to aid in the protection against corrosion

TA Recommendation: Open the manway and clean the accumulator for internal inspections.



#### PRESSURE VESSEL VISUAL INSPECTION REPORT

Jurisdiction #:

**155741-MD-29** 02/17/2012 3 of 11 155741

Matrix\_Inspection

LSD: 12-

12-29-096-11W6

A3090903

# Internal Inspection Results – VI N/A (Not Applicable)

Item	N/A	Condition	Comment (Check Status Bar or Press F1 for Help)	NCR	Action Item Integrity	Action Item Maintenance
Shell			No Internal Inspection Carried Out			
Heads	$\boxtimes$		No Internal Inspection Carried Out			
Manway	$\boxtimes$		No Internal Inspection Carried Out			
Gasket Surfaces	$\boxtimes$		No Internal Inspection Carried Out			
Welds	$\boxtimes$		No Internal Inspection Carried Out			
Refractory	$\boxtimes$		No Internal Inspection Carried Out			
Heating Coils	$\boxtimes$		No Internal Inspection Carried Out			
Demister Pad	$\boxtimes$		No Internal Inspection Carried Out			
Vane Pack	$\boxtimes$		No Internal Inspection Carried Out			
Baffles	$\square$		No Internal Inspection Carried Out			
Trays	$\boxtimes$		No Internal Inspection Carried Out			
Filter	$\boxtimes$		No Internal Inspection Carried Out			
Internal Coating	$\square$		No Internal Inspection Carried Out			
Tubesheet	$\boxtimes$		No Internal Inspection Carried Out			
Tube Bundle	$\boxtimes$		No Internal Inspection Carried Out			

#### Internal Visual Observations

Insp. Company:

No Internal Inspection Carried Out

Recommendations:

No Internal Inspection Carried Out

			PRESSURE V	ESSEL		•	155741-MD-29
			VISUAL INSPE		Inspe	ect Date:	02/17/2012
Canadi	an Natural		REPORT			Page:	4 of 11
					•	o. Job #:	155741
	trix_Inspection	LSD:	12-29-096-11W6	Juriso	diction #:	A30	90903
Firetube Static Data N/A (							
Diameter: Not Applica			Thickness: Not Applic			Bend: Not	Applicable
Length: Not Applica	ble	Firetube D	Description: Not Applic	able			
Firetube NDE	UT 🗌 Repo	ort#: Not Applic	able E	T 🗌 Rep	ort#: Not	Applicable	
Performed:	MT 🗌 Repo	ort#: Not Applic	able R	T 🗌 Rep	ort#: Not	Applicable	
	PT 🗌 Repo	ort#: Not Applic	able Othe	er 🗌 Repo	ort#: Not	Applicable	
Firetube Inspection Results	S						
Item	N/A Condition	(0)-	Comment	-     -   - )	NCR	Action Item	Action Item
Burner			eck Status Bar or Press F1 fo	(Help)			Maintenance
Burner Stack			nspection Carried Out				
Flange (Throat)			nspection Carried Out				
Tube Sheet			nspection Carried Out				
Hot Side			nspection Carried Out				
Miter			nspection Carried Out				$\square$
Return Bend			nspection Carried Out				
Supports			nspection Carried Out				
Butt Welds			nspection Carried Out				
Fillet Welds	$\square$	No Firetube Ir	nspection Carried Out				
Firetube Visual Observation	20						
No Firetube Inspection Ca	arried Out						
Recommendations:							
No Firetube Inspection C	arried Out						

Canadian Natural	PRESSURE VESSEL Report #:   VISUAL INSPECTION Inspect Date:   REPORT Page:   Insp. Co. Job #: Page:		<b>155741-MD-29</b> 02/17/2012 5 of 11 155741
Insp. Company: <u>Matrix_Inspection</u> LSD:	12-29-096-11W6 Juris	diction #:	A3090903
Vessel NDE and Final Summary: UT 🛛 Report#: NDE Performed: MT 🗌 Report#: PT 🗌 Report#:	RT 🗌 Rep	ort#: ort#:	
Maxi-Trak Observations Summary (Summarize inspection re	esults Max 255 Characters):		
PSV #2 is on its side both PSVs are due for service Tape on flanges Weathered and chipped coating exposing base metal to n	ninor surface corrosion		
Maxi-Trak Recommendations Summary (Summarize Recon			
Service the PSVs and ensure PSV #2 is installed in an up Remove the tape from the flanges Clean and touch-up the coating to aid in the protection ag			
Actions Corrected at Time of Inspection: (If actions were correct	ed at the time of Inspection – note the correcte	d actions here.)	
Additional Visual Observations			
2 <sup>nd</sup> PSV is on its side and should be in an upright position			
Any other safety concerns or observations from associated	equipment: (for example associated	l piping, buildings,	pumps etc)
No additional safety concerns noted at the time of inspect	tion		



Insp. Company:

Matrix\_Inspection

12-29-096-11W6

Jurisdiction #: A3090903

155741

155741-MD-29

02/17/2012

6 of 11

### Thickness and Remaining Life Evaluation "Must be Completed"

LSD:

# MUST BE COMPLETED AND RESOLVED WITH CNRL IMMEDIATELY UPON DISCOVERY OF LOW WALL THICKNESS AREAS

Step 1: Was any thickness measurement location found to be less than (Nominal WT - Corrosion Allowance)?: No

If YES, proceed to Step 2; if NO, proceed to "Crack Evaluation" and "CNRL Criticality Designation".

Step 2: Which component(s) were found below (Nominal WT - Corrosion Allowance)?

Components found below Nom - CA:

Components						
N/A - N/A						
N/A - N/A						
N/A - N/A						
N/A - N/A						
N/A - N/A						

Perform Steps 3 - 8 for each component with actual thickness less than (Nominal WT - Corrosion Allowance).

Step 3: Describe Location and Extent of Corrosion:

Components	Location and Extent of Corrosion
N/A - N/A	Not Applicable for this Inspection
N/A - N/A	Not Applicable for this Inspection
N/A - N/A	Not Applicable for this Inspection
N/A - N/A	Not Applicable for this Inspection
N/A - N/A	Not Applicable for this Inspection

Notes:

Not Applicable for this Inspection

Step 4:

- For shells and nozzles, calculate minimum required thickness (T-min) as per ASME Section VIII UG-27.
- For heads, calculate minimum required thickness (T-min) as per ASME Section VIII UG-32.

Components	T-Min
N/A - N/A	N/A



Insp. Company:

Matrix\_Inspection

12-29-096-11W6

Jurisdiction #:

A3090903

155741-MD-29

02/17/2012

7 of 11

155741

#### Thickness and Remaining Life Evaluation (Continued)

Step 5: Is any measured thickness less than calculated minimum required thickness (T-min)? N/A

LSD:

If YES, complete Step 6 If NO, proceed to Step 7..

Step 6: Is nature and extent of pitting acceptable as per API 510? N/A

Step 7: Calculate Remaining Life as per API 510. How? (Find last reading; use nominal thickness if nothing available). Short Term Corrosion Rates and Long Term Corrosion Rates.

Components	Remaining Life (Yrs)
N/A - N/A	N/A

Step 8: Contact CNRL Integrity Coordinator to discuss above results.

- Name of CNRL contact: Not Applicable for this Inspection
- Date and time of conversation: Not Applicable for this Inspection

Summary/results of conversation: Not Applicable for this Inspection

# Crack Evaluation by Magnetic Particle or Alternative Inspection "Must be Completed"

#### MUST BE COMPLETED AND RESOLVED WITH CNRL IMMEDIATELY UPON DISCOVERY OF CRACK-LIKE INDICATIONS

Were any indications found to suggest the vessel contained cracks? N/A

If NO, proceed to "CNRL Criticality Designation".

If YES, Contact CNRL Integrity Coordinator to discuss results.

- Name of CNRL contact: Not Applicable for this Inspection
- Date and time of conversation: Not Applicable for this Inspection

Summary/results of conversation: Not Applicable for this Inspection



02/17/2012 8 of 11 155741

155741-MD-29

Insp. Company:

Matrix\_Inspection

12-29-096-11W6

Jurisdiction #:

A3090903

# CNRL Criticality Evaluation – "MUST BE COMPLETED"

The CNRL In-Service Pressure Vessel Inspector MUST answer all the following questions

LSD:

- 1. Is the vessel fit-for-service? : Yes
- 2. Was the measured thickness less than the calculated minimum required thickness (T-min) for any component?: No
- 3. Were MT indications found?: N/A
- 4. Was the remaining life less than 6 years for sour service vessels or less than 10 years for sweet service vessels?: No
- 5. Were NCR's or Action Items generated as a result of the inspection? : Yes
- 6. Were UT readings below (Nominal WT Corrosion Allowance) found? : No

#### Information on CNRL Owner User Program - Criticality Designation and Required Review

RED – Vessel Inspection Results are deemed RED if one of the following occurred:

- The measured thickness was less than the calculated minimum required thickness (T-min) for any component.
- MT indications were found.
- The remaining life was calculated to be less than 6 years for sour-service vessels or less than 10 years for sweet-service vessels.

RED inspection reports must be signed off by the CNRL Chief Inspector.

YELLOW – Vessel Inspection Results are deemed YELLOW if one or more of the following occurred:

- The vessel was declared NOT fit-for-service by the 3<sup>rd</sup> Party In-Service PV Inspector.
- NCR's or Action Items were generated as a result of the inspection.
- UT readings below (Nominal WT Corrosion Allowance) were found.

YELLOW inspection reports must be signed off by the CNRL Pressure Equipment Integrity Coordinator.

GREEN - Vessel Inspection Results are deemed GREEN if <u>all</u> of the following are true:

- The vessel was declared fit-for-service by the 3<sup>rd</sup> Party In-Service PV Inspector.
- UT readings below (Nominal WT Corrosion Allowance) were NOT found.
- MT indications were NOT found.
- NCR's or Action Items were NOT generated as a result of the VE inspection.

GREEN inspection reports must be signed off by the 3<sup>rd</sup> Party In-Service Pressure Vessel Inspector.

Critica	lity Designation			Yel	low			
Vehicle #:	501 Kms:			Inspector (Name):	Matthew B	Dickinson	PESL:	601
Time In:	00:00 Time Out:	00:00	Hrs	Inspector (Signature):			API:	39483
Time In:	00:00 Time Out:	00:00	Hrs	CNRL Coordinator (I	— Name):			
Personnel:	BI, LP			CNRL Coordinator (	Signature):			
Billing Info:	AFE :			CNRL Chief Inspecto	Or (Signature):	(I am in full agree	ement with rep	port contents)
						(I am in full agree	ement with rep	port contents)



Equipment Photographs:




#### 01 nameplate



02 overview





03 manway



04 minor surface corrosion





05 accumulator PSV



06 PSV on its side