FORM U-1A MANUFACTURER'S DATA REPORT FOR PRESSURE VESSELS

(Alternative Form for Single Chamber , Completely Shop or Field Fabricated Vessels Only) As Required by the Provisions of the ASME Code Rules, Section VIII, Division 1

1. Manufactured and certified by <u>Cryogenic Vessel Alternatives, 9528 Warren Road, Mont Belvieu, Texas</u> 77580													
2. Manufactured for Cal-Frac Well Services, Ltd., 411 8 th Avenue SW, Calgary, Alberta, Canada T2P 1E3 (Name and address of Purchaser)													
3. Location of Installation Unknown (Name and address of Porchaser) (Name and address)													
4. Type · Horizontal C63001					001	25-450 CA1			000 1630			2008	
4. Type Horizontal C63001 25-450 CA1000 1630 2008 (Horizontal or Vert., Tank) (Mfgr's. Serial No.) (CRN) (Drawing Number) (Nat'l. Bd. No.) (Year Built) 5. The chemical and physical properties of all parts meet the requirements of material specifications of the ASME BOILER AND PRESSURE VESSEL CODE													
	esign, construction										7		
to *** Addenda (Date)					**					** Special Service per UG-120(d)			
				Code Case Nos.									
6. Shell :	hell : SA516-70N Matl. (Spec. No., Grade)			Nom	8/5 . Thk. (in.)	Corr. Allow. (In.)			වර්" Diam. I.D. (ft. & in.)		44 8-1/2" Length (overall)(ft. & in.)		
7. Seam	s: type	type 1			100) ** ** (°E) Time (hr)			type1 Girth (Welded,Dbl.,Sngl.,Lap,Butt) R.T		FULL 6		
8. Heads : (a) Matl. SA516-70N (b) Matl. SA516-70N													
8. Heads	s . (a) Iviati	(a) Mati(S					(b) Mati.			(Spec. No., Grade)			
	Location (Top, Bottom, Ends)	Minimum Thickness		rosion wance	Crown Radius	Knuckle Radius	Elliptical	Ratio	Conical Apex Angle	Hemispherical Radius	Flat Diameter	Side To Pressure (Convex or Concave)	
(a)	Ends	.875		0	**	**	2:		**	**	**	CONCAVE	
(b)	Ends	.875		0	**	**	2:	1	**	**	**	CONCAVE	
If removable , bolts used (describe other fastening)******													
9. MAWP 325PSI ** at max.Temp. 115F ** °F									pec. No.,Grade, Size ,No.)				
.	9. MAWP 325PSI ** at max.Temp. 115F ** °F (internal) (external)												
Min. design metal temp20_ °F at HYDRO test pressure _ 495_ psi													
10. Nozzles, inspection and safety valve openings :													
Purpose (Inlet, Outlet, Drain) No.		Diam. or Size	} 		Matl.			M	rcement atl.	How Attached	Location		
	Rear Fill Front Fill	1 1	8" 6"		30 PIPE	SA106 C		.500		**	UW 16.1 (e) UW 16.1 (e)		
Fro	ont Vapor Line	1	2"		30 PIPE	SA106 C		.218		**	UW 16.1 (e)		
Vent Pipe/Pressure Relief		1	3"	SCH 8	30 PIPE	SA106 C	R B	.300		**	UW 16.1 (e)	Aft head	
	HP Gauge Line	2	.25"	SCH 8	30 PIPE	SA106 C	R B	.120		k*	UW 16.1 (e)	Aft head	
	nter Pipe Stub	1	2" 25.5"		30 PIPE	SA106 C		.218		**	UW 16.1 (e)		
	Studding Outlet	·	late	SA516 GI	R 70N	3.06		**	UW 16.1 (h)				
11. Supports : Skirt No Lugs ** Legs ** Other ** Attached HEADS WELDED (Where and How)													
						tified and sign	ned by C	ommis	sioned Inspecto	ors have been f		following items of the	
report:													
No Impact test required / UG-20 (f)													
The duplicate code tag attached to the outside of the vessel has the correct MDMT. CVA NCR 84-2009 corrects the code tag													
information with regards to MDMT.													
		-		CEF	RTIFICA	TE OF SH	OP / FI	ELD	COMPLIANO	CE			
We certi	fy that the stateme	ents made	in this re	eport are	correct an	d that all det	ails of de	sign,m	aterial.construc	ction, and workr		vessel conform to the	
ASME Code for Pressure Vessels, Section VIII, Division1."U" Certificate of Authorization No. 31,457 expires November 3,2011 Date Co. name Cryogenic Vessel Alternatives Signed :													
. (Manufacturer) (Representative)													
CERTIFICATE OF SHOP / FIELD COMPLIANCE Vessel constructed by: Cryogenic Vessel Alternatives at 9528 Warren Road, Mont Belvieu, TX 77580													
I, the undersigned, holding a valid commission issued by the National Board of Boiler and Pressure Vessel Inspectors and/or the State or Province of TEXAS													
and employed by Seneca Insurance Company have inspected the component described in this Manufacturer's Data Report on 12-5-08, and state that, to the best of my knowledge and belief, the Manufacturer has constructed this pressure vessel in accordance with ASME Code, Section VIII, Division 1.													
By signi	ng this certificate i	neither the	Inspect	or nor h	is employe	r makes any	warrant	y, expr	essed or implie	ed, concerning t	he pressure ve	ssel described in this	
	cturer's Data Repo Iny kind arising from					nor nis emp	ioyer sh	ali be li	able in any ma	nner tor any pe	rsonal injury or I	property damage or a	

Date: 3-12-001 Signed:

Commissions 9280AB