



NOTE:

- DRAIN LINES STRAPPED TO FUEL GAS LINES VIA U-BOLT. LINES ARE GLYCOL TRACED AND INSULATED TOGETHER.
- 100mm (4") A333 PIPE DERATED TO 32,915 kPag (4774 psig) TO ALLOW FOR FULL 1.5mm CORROSION ALLOWANCE.

REV	DATE	DESCRIPTION	ENG	LD	BY	CHK
2	2021-06-29	AS-BUILT			BDD	FLJ SDZ
1	2018-12-11	AS-BUILT			JNL	NL VKT
0	2017-11-15	ISSUED FOR CONSTRUCTION			JNL	NL VH
A	2017-09-21	ISSUED FOR APPROVAL			JNL	NL VH

STAMPS

CLIENT	PROJECT DESC.
 BIRCHILL Canada McINTOSH PERRY 2711 - 39 Avenue N.E. Calgary, AB T1Y 4T8 Tel: 403-261-4991 Fax: 403-266-2361 www.mcintoshperry.com	BRAZEAU RIVER 100/14-09 & 102/14-09-43-13 W5M PAD SITE EQUIP. <hr/> DRAWING DESC. LINE HEATER U-5000 PROCESS & INSTRUMENTATION DIAGRAM <hr/> LSID: 01-09-43-13 W5M

SCALE	CREATION DATE:	DRAWING No.	PROJ. No.	REV
N.T.S.	2021-07-27	10723-1004	11249	2