

QT Pro / Pro+ / Max 5-15 | QT-54

When performance and efficiency are in demand, Quincy's QT Series is the premier industrial piston air compressor. The splash-lubricated QT is built with a cast iron body for strength and durability and an aluminum head for optimal cooling and longevity. The QT delivers lasting value through industry leading performance and reliability.



1 Air Filter

2 Splash-lubricated Piston Pump

3 Oil Level Sight Glass

4 Induction Motor

5 Magnetic Starter

6 Pressure Switch and Gauge

7 Drain Valve

8 Receiver

QT 5-15 HP Reciprocating Air Compressors

The QT Series Is Best For:

- ✓ Professional and industrial applications requiring premium efficiency and reliability
- ✓ Aluminum head for optimal heat dissipation and increased life-span
- ✓ Available with Pro, Pro+ and Max or fully custom configured models
- ✓ Optimized valve design for the highest volumetric efficiency in the market

QT MODELS AND CONFIGURATIONS

HP	Phase	Voltage Options	Unit	Tank	Tank Size (Gal)	ACFM (Max Pressure)	RPM	Pump Model	Approx Ship Wt. (lbs)	LxWxH (In)
			Configuration							
3	1	230	Simplex	Vertical	60	10.8 (100PSI)	1180	QTS-3	290	30x23x68
5	1	230	Simplex	Vertical	60	18.4 (100PSI)	1028	QTS-5	345	31x23x68
5	1	230	Simplex	Vertical	60	15.2 (175PSI)	1350	QT-54	350	31x23x70
					80				417	
5	1, 3	200, 230, 460, 575	Simplex	Vertical	80	17.2 (175PSI)	658	QT1	680	35x28x77
				Horizontal						67x30x49
5	1, 3	200, 230, 460, 575	Duplex	Horizontal	120	17.2* (175PSI)	658	QT1 (x2)	994	79x34x54
				Vertical	80	23.6 (175PSI)	896	QT1	720	35x28x77
7.5	1, 3	200, 230, 460, 575	Simplex	Horizontal	120	23.6* (175PSI)	896	QT1 (x2)	1058	79x34x54
				Vertical	80	29.8 (165PSI)	1192	QT1	792	37x34x78
10S	1	230	Simplex	Horizontal	200	27* (165PSI)	1007	QT1 (x2)	1401	76x44x63
				Vertical	120	27 (165PSI)	1007	QT1	792	37x34x78
10S	3	200, 230, 460, 575	Simplex	Horizontal	200	29.8* (165PSI)	1192	QT1 (x2)	1401	76x44x63
				Vertical	120	29.8 (165PSI)	1192	QT1	792	37x34x78
10	3	200, 230, 460, 575	Simplex	Horizontal	200	36* (175PSI)	682	QT2 (x2)	1693	76x56x64
				Vertical	120	36 (175PSI)	682	QT2	900	49x34x78
15	3	200, 230, 460, 575	Simplex	Horizontal	200	51* (175PSI)	932	QT2 (x2)	1915	76x56x64
				Vertical	120	51 (175PSI)	932	QT2	995	71x30x55

*Performance shown per pump on duplex units

Fuel Type	HP	Engine Brand	Tank Configuration	Tank Size (Gal)	Splash Lubricated Model	ACFM @ 175 psig	RPM
Gas	9	Honda	Horizontal	30	QT-54	14.5	1300
Gas	11	Honda			QT1	18.7	622
	13	Honda			23.6	867	
	14	Kholer			23.6	867	



QT Pro Package 5-15 hp

- ODP Motor
- Motor Overload Protection
- Ball Valve Tank Drain
- Automatic Start/Stop 5 to 10 hp
- Dual Control on 15 hp
- NO Bull Extended Warranty Available

QT Pro + 5-15 hp

- ODP Motor
- Motor Overload Protection
- Automatic Tank Drain
- Automatic Start/Stop 5 to 10 hp
- Dual Control on 15 hp
- Low Oil Level Shutdown
- NO Bull Extended Warranty Available

QT Max Package 5-15 hp

- ODP Motor
- Motor Overload Protection
- Automatic Tank Drain
- Automatic Start/Stop 5 to 7.5 hp
- Dual Control on 10-15 hp
- Low Oil Level Shutdown
- Air Cooled Aftercooler
- NO Bull Extended Warranty Available



ENK Kit - 3/Quin-Gp D



* Must purchase associated kit at the same time as the compressor to receive warranty extension

WARRANTY INFORMATION

NO BULL

Optional NO BULL Warranty

Pro/Pro+/Max Package with Extended Warranty Kit

3-Year Pump/2-Year Package Warranty

OEM Parts/Fluids and Online Registration Required

