



Instrument Control Services
Pressure Relief Valve Inspection Report

☒ In Service ☐ Out of Service ☐ Cust. Stock/Spare ☐ Archive ☐ Unknown

Facility Operator CRC		Facility VENTURA BASIN (VAB)			
Tag ID PSV-5789A		Equipment #		Description TORREY COMP SKID	
Manufacturer Hydrosel		Model # 12BG7M0V00/D0		Serial Number 621901-1	
				Shop # ☒ N/A	
Inlet Size/Rating Size 1.5" Rating MNPT ☐ RF ☐ RTJ ☒ Thrd ☐ Clamp		Outlet Size/Rating Size 2" Rating FNPT ☐ RF ☐ RTJ ☒ Thrd ☐ Clamp		Code ☒ UV ☐ Non-coded	
				Type ☒ Spring ☐ Bellows ☐ Pilot ☐ Weight ☐ Weight/Pilot	
				Service ☐ Liquid ☒ Gas ☐ Air ☐ Steam	
				Capacity 5392 ☒ SCFM ☐ GPM ☐ PPH	
				Cap NB Cert ☒ Yes ☐ No ☐ Unknown	
Orifice Size G - .503		CDTP		Set Point 620	
				Back Pressure ☒ N/A	
				Car Seal Off ☒ N/A	
				Car Seal On ☒ N/A	

PSV Location/Condition Inspection Results

PSV Condition As Found ☒ Mfg Tag Attached ☐ Plugged ☒ Clean ☐ Leaking ☐ Fouled ☐ Block valve failure ☐ Other (See Comments)		Inlet Piping As Found ☐ Clean ☐ Plugged ☐ Fouled ☐ Pipe strain/poor alignment ☐ Other (See Comments)		Outlet Piping As Found ☐ Clean ☐ Plugged ☐ Fouled ☐ Pipe strain/poor alignment ☐ Other (See Comments)	
--	--	--	--	---	--

As Found Test Results

Leak Test Pressure ☒ N/A If <90% set pressure on a conventional vapor service or pilot valve, or <80% set pressure on conventional liquid service valve, internal inspection required.		1st Pop Test Pressure 627		Reset Pressure 444		Test Result ☒ Pass ☐ Fail ☐ Dangerous Fail		Test Media ☒ Nitrogen ☐ Liquid ☐ Air	
		2nd Pop Test Pressure 620		Reset Pressure 437		Dangerous fail if valve relieves: >= 110% set pressure for valves set >70 psig >-2 psig for valves set <= 70 psig			

Cleanliness Condition		Test Interval Effect		Cleanliness Condition		Mechanical Condition																																																															
<table><tr><td></td><td>A</td><td>B</td><td>C</td><td>D</td><td>E</td></tr><tr><td>I</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>II</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>III</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>IV</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>V</td><td></td><td></td><td></td><td></td><td></td></tr></table>			A	B	C	D	E	I						II						III						IV						V						<table><tr><td></td><td>Poor - Decrease Interval and Assess Root Cause</td></tr><tr><td></td><td>Average - Same Interval</td></tr><tr><td></td><td>Good - Increase Interval</td></tr></table>			Poor - Decrease Interval and Assess Root Cause		Average - Same Interval		Good - Increase Interval	<table><tr><td></td><td>A. Internal parts show heavy deposits or rust with obvious plugging of nozzle or seat</td></tr><tr><td></td><td>B. Internal parts show some heavy, loose deposits or rust (possibility of obstructing flow path)</td></tr><tr><td></td><td>C. Internal parts show layers of oily deposits, scale or rust</td></tr><tr><td></td><td>D. Internal parts show thin oily or sticky ct</td></tr><tr><td></td><td>E. Internal parts clean</td></tr></table>			A. Internal parts show heavy deposits or rust with obvious plugging of nozzle or seat		B. Internal parts show some heavy, loose deposits or rust (possibility of obstructing flow path)		C. Internal parts show layers of oily deposits, scale or rust		D. Internal parts show thin oily or sticky ct		E. Internal parts clean	<table><tr><td></td><td>I. Internal parts are broken, worn, or eroded beyond repair (extensive parts replacement or new valve required)</td></tr><tr><td></td><td>II. Internal parts show severe corrosion, erosion, pitting or galling (significant repair required)</td></tr><tr><td></td><td>III. Internal parts show corrosion, erosion or pitting (machining required - beyond normal wear and tear)</td></tr><tr><td></td><td>IV. Seat scratched or pitted, other internal parts show slight pitting</td></tr><tr><td></td><td>V. Internal parts in good condition, only minor lapping required</td></tr></table>			I. Internal parts are broken, worn, or eroded beyond repair (extensive parts replacement or new valve required)		II. Internal parts show severe corrosion, erosion, pitting or galling (significant repair required)		III. Internal parts show corrosion, erosion or pitting (machining required - beyond normal wear and tear)		IV. Seat scratched or pitted, other internal parts show slight pitting		V. Internal parts in good condition, only minor lapping required
	A	B	C	D	E																																																																
I																																																																					
II																																																																					
III																																																																					
IV																																																																					
V																																																																					
	Poor - Decrease Interval and Assess Root Cause																																																																				
	Average - Same Interval																																																																				
	Good - Increase Interval																																																																				
	A. Internal parts show heavy deposits or rust with obvious plugging of nozzle or seat																																																																				
	B. Internal parts show some heavy, loose deposits or rust (possibility of obstructing flow path)																																																																				
	C. Internal parts show layers of oily deposits, scale or rust																																																																				
	D. Internal parts show thin oily or sticky ct																																																																				
	E. Internal parts clean																																																																				
	I. Internal parts are broken, worn, or eroded beyond repair (extensive parts replacement or new valve required)																																																																				
	II. Internal parts show severe corrosion, erosion, pitting or galling (significant repair required)																																																																				
	III. Internal parts show corrosion, erosion or pitting (machining required - beyond normal wear and tear)																																																																				
	IV. Seat scratched or pitted, other internal parts show slight pitting																																																																				
	V. Internal parts in good condition, only minor lapping required																																																																				

As Left Test Results

Relief Pressure 620	Reset Pressure 437	Final 90% Leak Test Pressure ☒ Pass ☐ Fail
------------------------	-----------------------	--

Comments

Technician TAYLOR COOK (123) Date 8/8/2019



Component	N/A	Clean	Dirty	Plugged	Damaged	Lap	Machine	Comments
Mfg Tag								☐ Missing ☐ Illegible ☐ OK
Inlet		☐	☐	☐	☐	☐	☐	
Outlet		☐	☐	☐	☐	☐	☐	
Nozzle	☐	☐	☐	☐	☐	☐	☐	
Nozzle Ring	☐	☐	☐	☐	☐	☐	☐	
Disc Insert	☐	☐	☐	☐	☐	☐	☐	
Disc Holder	☐	☐	☐	☐	☐	☐	☐	
Spring/Washer Assy.	☐	☐	☐	☐	☐	☐	☐	
Guide	☐	☐	☐	☐	☐			
Guide Ring	☐	☐	☐	☐	☐			
Spindle	☐	☐	☐	☐	☐			
Bellows	☐	☐	☐	☐	☐			
Bonnet/Body	☐	☐	☐	☐	☐			
Soft Goods	☐	☐	☐	☐	☐			
Comp Screw/Jam Nut	☐	☐	☐	☐	☐			
Cap/Lift Lever	☐	☐	☐	☐	☐			
Spring Identification (Old)	PN			Color Code		Wire Size		Range
Spring Identification (New)	PN ☐ N/A			Color Code		Wire Size		Range

Component	As Found		As Left		PSV Condition Comment
Nozzle Ring					
Nozzle Seat Step					
Nozzle Face to Seat					
Nozzle Seat	OD	ID	OD	ID	Outlet Comment
Guide Ring					
Disc Seat Step					
Disc Back Face To Seat					
Spindle					

Technician	()	Date
------------	-----	------