

GENERAL NOTES: 1. QUANTITIES IN B.O.M. ARE FOR (1) UNIT. 2. ALL PIPING TO BE IN ACCORDANCE WITH THE LATEST EDITION OF ASME B31.3 PRESSURE PIPING CODE. 3. VESSEL TO BE FABRICATED TO THE LATEST EDITION OF ASME SECTION VIII, DIV. 1 PRESSURE VESSELS. 4. THREADED PIPING TO BE: SA-106B SMLS, 1"-SCH.80 (mn) 5. ALL FORGED STEEL FITTINGS TO BE: SA-105N, 3000# (mn) RATING. 6. TUBING DETAILS: 3/8" & ½" 316 STAINLESS STEEL TUBING c/w STAINLESS STEEL SWAGelok FITTINGS. 7. PAINTING SPEC: PACKAGE TO BE CLEANED TO 'SSPC-SP-6' COMMERCIAL BLAST 1st COAT PRIMER: ONE (1) COAT OF DEVCO FAST DRY PRIMER, TWO (2) COAT OF DEVCO GRAY ENAMEL. SKID FLOOR: TWO (2) COAT OF DEVCO GRAY ENAMEL. INTERNAL SURFACE PREPARATION: SSPC-SP3 (78" VESSEL ONLY) INTERNAL COATING: 10-12 MILS DEVCO 253 (78" VESSEL ONLY) 8. PROTECT ALL OPENINGS FOR SHIPMENT. 9. BOLTING TO BE SA-193-B7M STUDS w/ SA-194-2HM NUTS c/w 316SS FLEXITALLIC GASKET. 10. BUILDING SIZE: 47'-0" LG x 18'-0" WIDE BUILDING TYPE: SELF FRAMER BUILDING ROOF TYPE: GABLE WALL HEIGHTS: 14'-6" EAVES (17'-6" @ PEAK) EXTERIOR: 22 GAUGE GALVALUME INTERIOR: 24 GAUGE WHITE FLUTED ALUMINUM INSULATION: ROOF R40, WALLS R20, 4mil VAPOR BARRIER DOORS: ONE (1) 3'-0" x 7'-0" GREY STEEL MAIN DOOR c/w PANIC HARDWARE, CHECK CHAIN, CANOPY, WEATHER STRIPPING, 24" x 24" IWG WINDOW ONE (2) 6'-0" x 7'-0" GREY STEEL MAIN DOOR c/w PANIC HARDWARE, CHECK CHAIN, CANOPY, WEATHER STRIPPING, 24" x 24" IWG WINDOW WINDOWS: TWO (2) 38" x 36" DOUBLE GLAZED SLIDING WINDOW w/ SCREEN. FANS: TWO (2) ET20-1 XP EXHAUST FAN c/w HOOD VENTILATION: TWO (2) 24" x 24" Sq. ADJUSTABLE LOUVERS, c/w SLIDE & BIRD SCREEN BUILDING ADDERS: BUILDING c/w FULL LENGTH ICE RAKES, EAVES TROUGH w/ DOWN SPOUT AND DOOR CANOPIES FOR EACH DOOR, DOORS TO HAVE "SNIFFERS" 11. PACKAGE IS HYDRO TESTED @ 1.5 TIMES MAMP FOR 1/2 HOUR AT ROOM TEMPERATURE 12. BOTTOM OF SKID IS INSULATED WITH 3" POLYURETHANE SPRAY FOAM. 13. INSULATE MAWAY AND EXTERIOR VESSEL HEAD. ** 14. INLET PSV-1658-01 WILL PROTRUDE INTO CEILING. BUILDING CREW WILL HAVE TO MAKE APPROPRIATE MODIFICATIONS TO CEILING ABOVE INLET PSV-1658-01 ****				2 VALVE LIST <table> <tr> <th>VALVE NUMBER</th><th>QTY.</th><th>MANUFACTURER</th><th>DESCRIPTION</th></tr> <tr> <td>4"BA1A1S-CSO</td><td>1</td><td>MERIDIAN</td><td>4" 150# RF REG. PORT BALL VALVE, NACE, CSO</td></tr> <tr> <td>3"BA1B1S-CSO</td><td>1</td><td>MERIDIAN</td><td>3" 300# RF REG. PORT BALL VALVE, NACE, CSO</td></tr> <tr> <td>3"BA1B1S</td><td>6</td><td>MERIDIAN</td><td>3" 300# RF REG. PORT BALL VALVE, NACE</td></tr> <tr> <td>2"BA1B1S</td><td>15</td><td>MERIDIAN</td><td>2" 300# RF REG. PORT BALL VALVE, NACE</td></tr> <tr> <td>2"BA1B1S</td><td>4</td><td>MERIDIAN</td><td>2" 300# RF FULL PORT BALL VALVE, NACE</td></tr> <tr> <td>6"C1E1S</td><td>1</td><td>WHEATLEY</td><td>6" 900# RF SWING CHECK VALVE, NACE</td></tr> <tr> <td>3"C1B1S</td><td>2</td><td>WHEATLEY</td><td>3" 300# RF SWING CHECK VALVE, NACE</td></tr> <tr> <td>2"C1B1S</td><td>2</td><td>WHEATLEY</td><td>2" 300# RF SWING CHECK VALVE, NACE</td></tr> <tr> <td>2"Y1B1S</td><td>2</td><td>AB STRAINER</td><td>2" 300# RF Y-STRAINER, NACE</td></tr> <tr> <td>1"BAF5H1S</td><td>10</td><td>JAG</td><td>1" SW CL. 900# F.P. BALL VALVE, NACE</td></tr> <tr> <td>1/2"BAF5H1S</td><td>2</td><td>JAG</td><td>1/2" SW CL. 900# F.P. BALL VALVE, NACE</td></tr> <tr> <td>1"G1.5H1S</td><td>2</td><td>MERIDIAN</td><td>1" SW CL. 800# GLOBE VALVE, NACE</td></tr> <tr> <td>1"G1.5J1S</td><td>2</td><td>MERIDIAN</td><td>1" SW CL. 1500# GLOBE VALVE, NACE</td></tr> <tr> <td>1/2"C5H1S</td><td>2</td><td>WHEATLEY</td><td>1/2" SW CL. 800# SWING CHECK VALVE, NACE</td></tr> <tr> <td>3/4"BAF5H1S</td><td>6</td><td>JAG</td><td>3/4" SWxNPT CL. 800# F.P. BALL VALVE, NACE</td></tr> <tr> <td>1/2"BAF5H1S</td><td>2</td><td>JAG</td><td>1/2" SWxNPT CL. 800# F.P. BALL VALVE, NACE</td></tr> <tr> <td>1/2"BAF4M1S</td><td>6</td><td>MERIDIAN</td><td>1/2" NPT WOG (MAC2CF) F.P. BALL VALVE, NACE</td></tr> <tr> <td>1/2"BAF4N1S</td><td>3</td><td>WKM</td><td>1/2" NPT WKM 3000psi F.P. BALL VALVE, NACE</td></tr> <tr> <td>1"G1.4H1S</td><td>2</td><td>MERIDIAN</td><td>1" NPT CL. 800# GLOBE VALVE, NACE</td></tr> <tr> <td>1-1/2"BA4M1S</td><td>2</td><td>MERIDIAN</td><td>1-1/2" NPT BAR STOCK R.P. BALL VALVE, NACE</td></tr> <tr> <td>1"BA4M1S</td><td>5</td><td>MERIDIAN</td><td>1" NPT BAR STOCK R.P. BALL VALVE, NACE</td></tr> <tr> <td>3/4"BA4M1S</td><td>2</td><td>MERIDIAN</td><td>3/4" NPT BAR STOCK R.P. BALL VALVE, NACE</td></tr> <tr> <td>1/2"BA4M1S</td><td>15</td><td>MERIDIAN</td><td>1/2" NPT BAR STOCK R.P. BALL VALVE, NACE</td></tr> <tr> <td>1/4"BA4M1S</td><td>13</td><td>MERIDIAN</td><td>1/4" NPT BAR STOCK R.P. BALL VALVE, NACE</td></tr> <tr> <td>1"C4M1S</td><td>4</td><td>WHEATLEY</td><td>1" NPT 2000# SWING CHECK VALVE, NACE</td></tr> <tr> <td>1/2"NE4P1S</td><td>10</td><td>CENTURY</td><td>1/2" NPT 6000# S.S. FxP NEEDLE VALVE</td></tr> <tr> <td>1/4"NE4P1S</td><td>1</td><td>CENTURY</td><td>1/4" NPT 6000# S.S. FxP NEEDLE VALVE</td></tr> </table>				VALVE NUMBER	QTY.	MANUFACTURER	DESCRIPTION	4"BA1A1S-CSO	1	MERIDIAN	4" 150# RF REG. PORT BALL VALVE, NACE, CSO	3"BA1B1S-CSO	1	MERIDIAN	3" 300# RF REG. PORT BALL VALVE, NACE, CSO	3"BA1B1S	6	MERIDIAN	3" 300# RF REG. PORT BALL VALVE, NACE	2"BA1B1S	15	MERIDIAN	2" 300# RF REG. PORT BALL VALVE, NACE	2"BA1B1S	4	MERIDIAN	2" 300# RF FULL PORT BALL VALVE, NACE	6"C1E1S	1	WHEATLEY	6" 900# RF SWING CHECK VALVE, NACE	3"C1B1S	2	WHEATLEY	3" 300# RF SWING CHECK VALVE, NACE	2"C1B1S	2	WHEATLEY	2" 300# RF SWING CHECK VALVE, NACE	2"Y1B1S	2	AB STRAINER	2" 300# RF Y-STRAINER, NACE	1"BAF5H1S	10	JAG	1" SW CL. 900# F.P. BALL VALVE, NACE	1/2"BAF5H1S	2	JAG	1/2" SW CL. 900# F.P. BALL VALVE, NACE	1"G1.5H1S	2	MERIDIAN	1" SW CL. 800# GLOBE VALVE, NACE	1"G1.5J1S	2	MERIDIAN	1" SW CL. 1500# GLOBE VALVE, NACE	1/2"C5H1S	2	WHEATLEY	1/2" SW CL. 800# SWING CHECK VALVE, NACE	3/4"BAF5H1S	6	JAG	3/4" SWxNPT CL. 800# F.P. BALL VALVE, NACE	1/2"BAF5H1S	2	JAG	1/2" SWxNPT CL. 800# F.P. BALL VALVE, NACE	1/2"BAF4M1S	6	MERIDIAN	1/2" NPT WOG (MAC2CF) F.P. BALL VALVE, NACE	1/2"BAF4N1S	3	WKM	1/2" NPT WKM 3000psi F.P. BALL VALVE, NACE	1"G1.4H1S	2	MERIDIAN	1" NPT CL. 800# GLOBE VALVE, NACE	1-1/2"BA4M1S	2	MERIDIAN	1-1/2" NPT BAR STOCK R.P. BALL VALVE, NACE	1"BA4M1S	5	MERIDIAN	1" NPT BAR STOCK R.P. BALL VALVE, NACE	3/4"BA4M1S	2	MERIDIAN	3/4" NPT BAR STOCK R.P. BALL VALVE, NACE	1/2"BA4M1S	15	MERIDIAN	1/2" NPT BAR STOCK R.P. BALL VALVE, NACE	1/4"BA4M1S	13	MERIDIAN	1/4" NPT BAR STOCK R.P. BALL VALVE, NACE	1"C4M1S	4	WHEATLEY	1" NPT 2000# SWING CHECK VALVE, NACE	1/2"NE4P1S	10	CENTURY	1/2" NPT 6000# S.S. FxP NEEDLE VALVE	1/4"NE4P1S	1	CENTURY	1/4" NPT 6000# S.S. FxP NEEDLE VALVE	4																																																																																															
VALVE NUMBER	QTY.	MANUFACTURER	DESCRIPTION																																																																																																																																																																																																																				
4"BA1A1S-CSO	1	MERIDIAN	4" 150# RF REG. PORT BALL VALVE, NACE, CSO																																																																																																																																																																																																																				
3"BA1B1S-CSO	1	MERIDIAN	3" 300# RF REG. PORT BALL VALVE, NACE, CSO																																																																																																																																																																																																																				
3"BA1B1S	6	MERIDIAN	3" 300# RF REG. PORT BALL VALVE, NACE																																																																																																																																																																																																																				
2"BA1B1S	15	MERIDIAN	2" 300# RF REG. PORT BALL VALVE, NACE																																																																																																																																																																																																																				
2"BA1B1S	4	MERIDIAN	2" 300# RF FULL PORT BALL VALVE, NACE																																																																																																																																																																																																																				
6"C1E1S	1	WHEATLEY	6" 900# RF SWING CHECK VALVE, NACE																																																																																																																																																																																																																				
3"C1B1S	2	WHEATLEY	3" 300# RF SWING CHECK VALVE, NACE																																																																																																																																																																																																																				
2"C1B1S	2	WHEATLEY	2" 300# RF SWING CHECK VALVE, NACE																																																																																																																																																																																																																				
2"Y1B1S	2	AB STRAINER	2" 300# RF Y-STRAINER, NACE																																																																																																																																																																																																																				
1"BAF5H1S	10	JAG	1" SW CL. 900# F.P. BALL VALVE, NACE																																																																																																																																																																																																																				
1/2"BAF5H1S	2	JAG	1/2" SW CL. 900# F.P. BALL VALVE, NACE																																																																																																																																																																																																																				
1"G1.5H1S	2	MERIDIAN	1" SW CL. 800# GLOBE VALVE, NACE																																																																																																																																																																																																																				
1"G1.5J1S	2	MERIDIAN	1" SW CL. 1500# GLOBE VALVE, NACE																																																																																																																																																																																																																				
1/2"C5H1S	2	WHEATLEY	1/2" SW CL. 800# SWING CHECK VALVE, NACE																																																																																																																																																																																																																				
3/4"BAF5H1S	6	JAG	3/4" SWxNPT CL. 800# F.P. BALL VALVE, NACE																																																																																																																																																																																																																				
1/2"BAF5H1S	2	JAG	1/2" SWxNPT CL. 800# F.P. BALL VALVE, NACE																																																																																																																																																																																																																				
1/2"BAF4M1S	6	MERIDIAN	1/2" NPT WOG (MAC2CF) F.P. BALL VALVE, NACE																																																																																																																																																																																																																				
1/2"BAF4N1S	3	WKM	1/2" NPT WKM 3000psi F.P. BALL VALVE, NACE																																																																																																																																																																																																																				
1"G1.4H1S	2	MERIDIAN	1" NPT CL. 800# GLOBE VALVE, NACE																																																																																																																																																																																																																				
1-1/2"BA4M1S	2	MERIDIAN	1-1/2" NPT BAR STOCK R.P. BALL VALVE, NACE																																																																																																																																																																																																																				
1"BA4M1S	5	MERIDIAN	1" NPT BAR STOCK R.P. BALL VALVE, NACE																																																																																																																																																																																																																				
3/4"BA4M1S	2	MERIDIAN	3/4" NPT BAR STOCK R.P. BALL VALVE, NACE																																																																																																																																																																																																																				
1/2"BA4M1S	15	MERIDIAN	1/2" NPT BAR STOCK R.P. BALL VALVE, NACE																																																																																																																																																																																																																				
1/4"BA4M1S	13	MERIDIAN	1/4" NPT BAR STOCK R.P. BALL VALVE, NACE																																																																																																																																																																																																																				
1"C4M1S	4	WHEATLEY	1" NPT 2000# SWING CHECK VALVE, NACE																																																																																																																																																																																																																				
1/2"NE4P1S	10	CENTURY	1/2" NPT 6000# S.S. FxP NEEDLE VALVE																																																																																																																																																																																																																				
1/4"NE4P1S	1	CENTURY	1/4" NPT 6000# S.S. FxP NEEDLE VALVE																																																																																																																																																																																																																				
7 <table> <tr> <th>TAG</th><th>QTY</th><th>MAKE</th><th>DESCRIPTION</th></tr> <tr> <td>FM-1658-04</td><td>2</td><td>ROOTS</td><td>ROTARY FLOW METER, 8C175 ROTARY METER, 1½" MNPT END CONNECTIONS, METRIC DISPLAY, 175 MAMP</td></tr> <tr> <td>FE-1658-03</td><td>2</td><td>NUFLO</td><td>TURBINE METER: 1.5" x 2" EZ-IN STD STYLE ASSEMBLY, 151 TO 6000 BPD</td></tr> <tr> <td>FQIT-1658-03</td><td></td><td></td><td>c/w 2" 600# KIT ASSEMBLY</td></tr> <tr> <td>FQIT-1658-04</td><td></td><td></td><td>TOTALIZER: NUFLO MC-III FLOW ANALYZER, LOCAL DISPLAY, CSA XPROOF, CLASS 1 DIV 1, 4-20mA LOOP, MODBUS RS-485</td></tr> <tr> <td>PCV-1658-XX (TP)</td><td>10</td><td>FISHER</td><td>67CGR-362 INSTRUMENT GAS REGULATOR, ¼" FNPT CONNECTIONS, STANDARD SERVICE TRIM, 5 TO 35psig SPRING RANGE, 250psig MAMP</td></tr> <tr> <td>PCV-1658-XX (TP)</td><td>4</td><td>FISHER</td><td>67CGR-601 INSTRUMENT GAS REGULATOR, ¼" FNPT CONNECTIONS, STANDARD SERVICE TRIM, 0 TO 125psig SPRING RANGE, 250psig MAMP</td></tr> <tr> <td>PI-1658-01</td><td>2</td><td>WESTERN GAUGE (WG)</td><td>ELITE PRESSURE GAUGE, SS1F, ½" NPT BTM x 4" FACE, 0-1000psig RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, SOUR. SERVICE</td></tr> <tr> <td>PI-1658-03</td><td></td><td></td><td>ELITE PRESSURE GAUGE, SS1F, ½" NPT BTM x 4" FACE, 0-1000psig RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, SOUR. SERVICE</td></tr> <tr> <td>PI-1658-05</td><td>1</td><td>WESTERN GAUGE (WG)</td><td>ELITE PRESSURE GAUGE, SS1F, ½" NPT BTM x 4" FACE, 0-1500psig RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, SOUR. SERVICE</td></tr> <tr> <td>PI-1658-04</td><td>1</td><td>WESTERN GAUGE (WG)</td><td>ELITE PRESSURE GAUGE, LF, ½" NPT BTM x 2½" FACE, 0-200psig RANGE, DUAL SCALE, MOUNTED ON FUEL GAS SCRUBBER, STD. SERVICE</td></tr> <tr> <td>TI-1658-01</td><td>1</td><td>WESTERN GAUGE (WG)</td><td>MASTER TEMP. TEMPERATURE INDICATOR, ½" BCM x 3" FACE x 6" STEM, -40 TO 160°F TEMP. RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, c/w ½" FNPT x ¾" MNPT x 6" "U" DIMENSION LENGTH, 316SST THERMOWELL</td></tr> <tr> <td>LG-1658-01a</td><td>2</td><td>QUALITY</td><td>LEVEL GAUGE, 019R20 RELEX SIGHT GLASS, MAMP: 2000psig @ 100°F, MOUNTED ON 6" BRIDLES, 12.625" VISIBLE GLASS, 17.625" MIN. CENTERS</td></tr> <tr> <td>LG-1658-02a</td><td></td><td></td><td>LEVEL GAUGE, 019R20 RELEX SIGHT GLASS, MAMP: 2000psig @ 100°F, MOUNTED ON 6" BRIDLES, 12.625" VISIBLE GLASS, 17.625" MIN. CENTERS</td></tr> <tr> <td>LG-1658-04</td><td>1</td><td>QUALITY</td><td>LEVEL GAUGE, 015R20 REFLEX SIGHT GLASS, MAMP: 1500psig @ 100°F, MOUNTED IN LIQUID/GAS INTERFACE, c/w (1) SET OF 0146 GAUGE VALVES, NACE MR0175-2002</td></tr> <tr> <td>LI-1658-05</td><td>1</td><td>PLAINSMAN</td><td>METHANOL LEVEL GAUGE, P5700-52-48-CTM, MAMP: 140psig, ½" NPT CONNECTIONS, 4'-0" LONG, METRIC HEIGHT/RATE</td></tr> <tr> <td>EBDV-1658-07</td><td>1</td><td>FISHER</td><td>D4 CONTROL VALVE 1" NPT, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi</td></tr> <tr> <td>EBDV-1658-06</td><td>1</td><td>FISHER</td><td>D4 CONTROL VALVE 1" 1500# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi</td></tr> <tr> <td>LG-1658-01b,c</td><td>3</td><td>QUALITY</td><td>LEVEL GAUGE, 019R20 TRANSPARENT SIGHT GLASS, MAMP: 2000psig @ 100°F, MOUNTED ON 6" BRIDLES, 12.625" VISIBLE GLASS, 17.625" MIN. CENTERS</td></tr> </table>				TAG	QTY	MAKE	DESCRIPTION	FM-1658-04	2	ROOTS	ROTARY FLOW METER, 8C175 ROTARY METER, 1½" MNPT END CONNECTIONS, METRIC DISPLAY, 175 MAMP	FE-1658-03	2	NUFLO	TURBINE METER: 1.5" x 2" EZ-IN STD STYLE ASSEMBLY, 151 TO 6000 BPD	FQIT-1658-03			c/w 2" 600# KIT ASSEMBLY	FQIT-1658-04			TOTALIZER: NUFLO MC-III FLOW ANALYZER, LOCAL DISPLAY, CSA XPROOF, CLASS 1 DIV 1, 4-20mA LOOP, MODBUS RS-485	PCV-1658-XX (TP)	10	FISHER	67CGR-362 INSTRUMENT GAS REGULATOR, ¼" FNPT CONNECTIONS, STANDARD SERVICE TRIM, 5 TO 35psig SPRING RANGE, 250psig MAMP	PCV-1658-XX (TP)	4	FISHER	67CGR-601 INSTRUMENT GAS REGULATOR, ¼" FNPT CONNECTIONS, STANDARD SERVICE TRIM, 0 TO 125psig SPRING RANGE, 250psig MAMP	PI-1658-01	2	WESTERN GAUGE (WG)	ELITE PRESSURE GAUGE, SS1F, ½" NPT BTM x 4" FACE, 0-1000psig RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, SOUR. SERVICE	PI-1658-03			ELITE PRESSURE GAUGE, SS1F, ½" NPT BTM x 4" FACE, 0-1000psig RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, SOUR. SERVICE	PI-1658-05	1	WESTERN GAUGE (WG)	ELITE PRESSURE GAUGE, SS1F, ½" NPT BTM x 4" FACE, 0-1500psig RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, SOUR. SERVICE	PI-1658-04	1	WESTERN GAUGE (WG)	ELITE PRESSURE GAUGE, LF, ½" NPT BTM x 2½" FACE, 0-200psig RANGE, DUAL SCALE, MOUNTED ON FUEL GAS SCRUBBER, STD. SERVICE	TI-1658-01	1	WESTERN GAUGE (WG)	MASTER TEMP. TEMPERATURE INDICATOR, ½" BCM x 3" FACE x 6" STEM, -40 TO 160°F TEMP. RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, c/w ½" FNPT x ¾" MNPT x 6" "U" DIMENSION LENGTH, 316SST THERMOWELL	LG-1658-01a	2	QUALITY	LEVEL GAUGE, 019R20 RELEX SIGHT GLASS, MAMP: 2000psig @ 100°F, MOUNTED ON 6" BRIDLES, 12.625" VISIBLE GLASS, 17.625" MIN. CENTERS	LG-1658-02a			LEVEL GAUGE, 019R20 RELEX SIGHT GLASS, MAMP: 2000psig @ 100°F, MOUNTED ON 6" BRIDLES, 12.625" VISIBLE GLASS, 17.625" MIN. CENTERS	LG-1658-04	1	QUALITY	LEVEL GAUGE, 015R20 REFLEX SIGHT GLASS, MAMP: 1500psig @ 100°F, MOUNTED IN LIQUID/GAS INTERFACE, c/w (1) SET OF 0146 GAUGE VALVES, NACE MR0175-2002	LI-1658-05	1	PLAINSMAN	METHANOL LEVEL GAUGE, P5700-52-48-CTM, MAMP: 140psig, ½" NPT CONNECTIONS, 4'-0" LONG, METRIC HEIGHT/RATE	EBDV-1658-07	1	FISHER	D4 CONTROL VALVE 1" NPT, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi	EBDV-1658-06	1	FISHER	D4 CONTROL VALVE 1" 1500# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi	LG-1658-01b,c	3	QUALITY	LEVEL GAUGE, 019R20 TRANSPARENT SIGHT GLASS, MAMP: 2000psig @ 100°F, MOUNTED ON 6" BRIDLES, 12.625" VISIBLE GLASS, 17.625" MIN. CENTERS	7 <table> <tr> <th>TAG</th><th>QTY</th><th>MAKE</th><th>DESCRIPTION</th></tr> <tr> <td>PSV-1658-01</td><td>1</td><td>FARRIS</td><td>PRESSURE SAFETY VALVE, MODEL 26KA12-120 3" 300# RF x 4" 150# RF, 1" ORIFICE, SOUR PRESSURE SERVICE TRIM, SET @ 720psig</td></tr> <tr> <td>PSV-1658-02</td><td>2</td><td>SWAGelok</td><td>PRESSURE SAFETY VALVE, SS4R-3A5, ½" MNPT INLET x ¼" FNPT OUTLET, 316SS BODY, SET @ 720psig, MOUNTED ON METHANOL PUMPS</td></tr> <tr> <td>PSV-1658-04</td><td>1</td><td>MERCER</td><td>PRESSURE SAFETY VALVE, MODEL 9100, 2" NPT INLET x 2" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 1440psig</td></tr> <tr> <td>PSV-1658-05</td><td>1</td><td>MERCER</td><td>PRESSURE SAFETY VALVE, MODEL 9100, 1" NPT INLET x 1" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 150psig</td></tr> <tr> <td>LSHH-1658-01</td><td>4</td><td>MURPHY</td><td>ELECTRIC LEVEL SWITCH, LS200S5, 2" MNPT, NACE, 3116SS BODY, RATED FOR 2000psi, 304SS FLOAT @ 0.5 SG, SPDT SNAP ACTING, CLASS 1 DIV 1</td></tr> <tr> <td>LSLL-1658-01</td><td></td><td></td><td>LSLL-1658-01</td></tr> <tr> <td>LSLL-1658-02</td><td></td><td></td><td>LSLL-1658-02</td></tr> <tr> <td>LSHH-1658-04</td><td></td><td></td><td>LSHH-1658-04</td></tr> <tr> <td>PT-1658-01</td><td>4</td><td>ROSEMOUNT</td><td>ROSEMOUNT 2088 PRESSURE TRANSMITTER P/n. 208863522A1B4C6</td></tr> <tr> <td>PT-1658-02/03</td><td></td><td></td><td>PT-1658-02/03</td></tr> <tr> <td>PT-1658-04</td><td></td><td></td><td>PT-1658-04</td></tr> <tr> <td>ESDV-1658-01</td><td>3</td><td>NUTRON</td><td>BALL VALVE, 3" 300#, FLOATER STYLE RF RP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC MODEL: ES0350.02D04A.27K2</td></tr> <tr> <td>ESDV-1658-02</td><td></td><td></td><td>ESDV-1658-02</td></tr> <tr> <td>ESDV-1658-05</td><td></td><td></td><td>ESDV-1658-05</td></tr> <tr> <td>EBDV-1658-04</td><td>1</td><td>FISHER</td><td>D4 CONTROL VALVE 1" 300# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi</td></tr> <tr> <td>EBDV-1658-03</td><td>1</td><td>FISHER</td><td>D4 CONTROL VALVE 1" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi</td></tr> <tr> <td>PV-1658-01</td><td>1</td><td>CVS CONTROLS</td><td>667-4-70 "EW" 12"x8" 600# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SOUR PROCESS, SIZE 70 ACTUATOR, NACE SERVICE, 6-30psi SUPPLY, ATO/FC</td></tr> <tr> <td>PV-1658-01</td><td></td><td></td><td>c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE</td></tr> <tr> <td>PV-1658-03</td><td>1</td><td>CVS CONTROLS</td><td>CONTROL VALVE: 667-4-70 "EW" 12"x8" 300# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SIZE 70 ACTUATOR, 6-30psi SUPPLY, ATO/FC, BOTH NACE SERVICE</td></tr> <tr> <td>PV-1658-03</td><td></td><td></td><td>c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE</td></tr> <tr> <td>ESDV-1658-08</td><td>1</td><td>NUTRON</td><td>BALL VALVE, 2" 600#, FLOATER STYLE RF FP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC</td></tr> <tr> <td>LV-1658-01</td><td>1</td><td>FISHER</td><td>D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE</td></tr> <tr> <td>LV-1658-02</td><td>1</td><td>FISHER</td><td>D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 1" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE</td></tr> <tr> <td>LV-1658-03</td><td>1</td><td>FISHER</td><td>D2 FLOPRO LIQUID CONTROL VALVE, 1" FNPT END CONNECTIONS, STANDARD NACE SERVICE, 3-15psi SUPPLY, AIR TO OPEN/FC, RATED: 2250psi @ 200°F</td></tr> <tr> <td>LY-1658-01</td><td>2</td><td>FISHER</td><td>I2P-100 TRANSDUCER, 4-20mA INPUT, 2-33psi FIELD SELECTABLE OUTPUT, FACTORY APPROVED, CSA APPROVED, X-PROOF, CLASS 1 DIV. 1,</td></tr> <tr> <td>LY-1658-02</td><td></td><td></td><td>LY-1658-02</td></tr> <tr> <td>LC-1658-03</td><td>1</td><td>FISHER</td><td>L2 LIQUID LEVEL CONTROLLER, 2" NPT PROCESS CONNECTION, STANDARD NACE SERVICE, SNAP ACTING CONTROL, DIRECT ACTING INSTRUMENT SIGNAL, 35psi SUPPLY, PNEUMATIC</td></tr> <tr> <td>ESDV-1658-01</td><td>4</td><td>ASCO</td><td>EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF, MOP: 115psig</td></tr> <tr> <td>EBDV-1658-03</td><td>4</td><td>ASCO</td><td>EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF</td></tr> <tr> <td>FE-1658-01</td><td>1</td><td>DANIEL</td><td>12" 300# SCH. 80 SENIOR METER RUN, NACE PROCESS, 224" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT</td></tr> <tr> <td>FE-1658-02</td><td>1</td><td>DANIEL</td><td>6" 900# SCH. 160 SENIOR METER RUN, NACE PROCESS, 118" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT</td></tr> <tr> <td>FE-1658-05</td><td>1</td><td>DANIEL</td><td>2" 600# SCH. 80 SENIOR METER RUN, NACE PROCESS, 48" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT</td></tr> </table>				TAG	QTY	MAKE	DESCRIPTION	PSV-1658-01	1	FARRIS	PRESSURE SAFETY VALVE, MODEL 26KA12-120 3" 300# RF x 4" 150# RF, 1" ORIFICE, SOUR PRESSURE SERVICE TRIM, SET @ 720psig	PSV-1658-02	2	SWAGelok	PRESSURE SAFETY VALVE, SS4R-3A5, ½" MNPT INLET x ¼" FNPT OUTLET, 316SS BODY, SET @ 720psig, MOUNTED ON METHANOL PUMPS	PSV-1658-04	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 2" NPT INLET x 2" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 1440psig	PSV-1658-05	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 1" NPT INLET x 1" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 150psig	LSHH-1658-01	4	MURPHY	ELECTRIC LEVEL SWITCH, LS200S5, 2" MNPT, NACE, 3116SS BODY, RATED FOR 2000psi, 304SS FLOAT @ 0.5 SG, SPDT SNAP ACTING, CLASS 1 DIV 1	LSLL-1658-01			LSLL-1658-01	LSLL-1658-02			LSLL-1658-02	LSHH-1658-04			LSHH-1658-04	PT-1658-01	4	ROSEMOUNT	ROSEMOUNT 2088 PRESSURE TRANSMITTER P/n. 208863522A1B4C6	PT-1658-02/03			PT-1658-02/03	PT-1658-04			PT-1658-04	ESDV-1658-01	3	NUTRON	BALL VALVE, 3" 300#, FLOATER STYLE RF RP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC MODEL: ES0350.02D04A.27K2	ESDV-1658-02			ESDV-1658-02	ESDV-1658-05			ESDV-1658-05	EBDV-1658-04	1	FISHER	D4 CONTROL VALVE 1" 300# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi	EBDV-1658-03	1	FISHER	D4 CONTROL VALVE 1" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi	PV-1658-01	1	CVS CONTROLS	667-4-70 "EW" 12"x8" 600# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SOUR PROCESS, SIZE 70 ACTUATOR, NACE SERVICE, 6-30psi SUPPLY, ATO/FC	PV-1658-01			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE	PV-1658-03	1	CVS CONTROLS	CONTROL VALVE: 667-4-70 "EW" 12"x8" 300# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SIZE 70 ACTUATOR, 6-30psi SUPPLY, ATO/FC, BOTH NACE SERVICE	PV-1658-03			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE	ESDV-1658-08	1	NUTRON	BALL VALVE, 2" 600#, FLOATER STYLE RF FP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC	LV-1658-01	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE	LV-1658-02	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 1" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE	LV-1658-03	1	FISHER	D2 FLOPRO LIQUID CONTROL VALVE, 1" FNPT END CONNECTIONS, STANDARD NACE SERVICE, 3-15psi SUPPLY, AIR TO OPEN/FC, RATED: 2250psi @ 200°F	LY-1658-01	2	FISHER	I2P-100 TRANSDUCER, 4-20mA INPUT, 2-33psi FIELD SELECTABLE OUTPUT, FACTORY APPROVED, CSA APPROVED, X-PROOF, CLASS 1 DIV. 1,	LY-1658-02			LY-1658-02	LC-1658-03	1	FISHER	L2 LIQUID LEVEL CONTROLLER, 2" NPT PROCESS CONNECTION, STANDARD NACE SERVICE, SNAP ACTING CONTROL, DIRECT ACTING INSTRUMENT SIGNAL, 35psi SUPPLY, PNEUMATIC	ESDV-1658-01	4	ASCO	EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF, MOP: 115psig	EBDV-1658-03	4	ASCO	EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF	FE-1658-01	1	DANIEL	12" 300# SCH. 80 SENIOR METER RUN, NACE PROCESS, 224" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT	FE-1658-02	1	DANIEL	6" 900# SCH. 160 SENIOR METER RUN, NACE PROCESS, 118" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT	FE-1658-05	1	DANIEL	2" 600# SCH. 80 SENIOR METER RUN, NACE PROCESS, 48" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT
TAG	QTY	MAKE	DESCRIPTION																																																																																																																																																																																																																				
FM-1658-04	2	ROOTS	ROTARY FLOW METER, 8C175 ROTARY METER, 1½" MNPT END CONNECTIONS, METRIC DISPLAY, 175 MAMP																																																																																																																																																																																																																				
FE-1658-03	2	NUFLO	TURBINE METER: 1.5" x 2" EZ-IN STD STYLE ASSEMBLY, 151 TO 6000 BPD																																																																																																																																																																																																																				
FQIT-1658-03			c/w 2" 600# KIT ASSEMBLY																																																																																																																																																																																																																				
FQIT-1658-04			TOTALIZER: NUFLO MC-III FLOW ANALYZER, LOCAL DISPLAY, CSA XPROOF, CLASS 1 DIV 1, 4-20mA LOOP, MODBUS RS-485																																																																																																																																																																																																																				
PCV-1658-XX (TP)	10	FISHER	67CGR-362 INSTRUMENT GAS REGULATOR, ¼" FNPT CONNECTIONS, STANDARD SERVICE TRIM, 5 TO 35psig SPRING RANGE, 250psig MAMP																																																																																																																																																																																																																				
PCV-1658-XX (TP)	4	FISHER	67CGR-601 INSTRUMENT GAS REGULATOR, ¼" FNPT CONNECTIONS, STANDARD SERVICE TRIM, 0 TO 125psig SPRING RANGE, 250psig MAMP																																																																																																																																																																																																																				
PI-1658-01	2	WESTERN GAUGE (WG)	ELITE PRESSURE GAUGE, SS1F, ½" NPT BTM x 4" FACE, 0-1000psig RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, SOUR. SERVICE																																																																																																																																																																																																																				
PI-1658-03			ELITE PRESSURE GAUGE, SS1F, ½" NPT BTM x 4" FACE, 0-1000psig RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, SOUR. SERVICE																																																																																																																																																																																																																				
PI-1658-05	1	WESTERN GAUGE (WG)	ELITE PRESSURE GAUGE, SS1F, ½" NPT BTM x 4" FACE, 0-1500psig RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, SOUR. SERVICE																																																																																																																																																																																																																				
PI-1658-04	1	WESTERN GAUGE (WG)	ELITE PRESSURE GAUGE, LF, ½" NPT BTM x 2½" FACE, 0-200psig RANGE, DUAL SCALE, MOUNTED ON FUEL GAS SCRUBBER, STD. SERVICE																																																																																																																																																																																																																				
TI-1658-01	1	WESTERN GAUGE (WG)	MASTER TEMP. TEMPERATURE INDICATOR, ½" BCM x 3" FACE x 6" STEM, -40 TO 160°F TEMP. RANGE, DUAL SCALE, MOUNTED ON INLET VESSEL, c/w ½" FNPT x ¾" MNPT x 6" "U" DIMENSION LENGTH, 316SST THERMOWELL																																																																																																																																																																																																																				
LG-1658-01a	2	QUALITY	LEVEL GAUGE, 019R20 RELEX SIGHT GLASS, MAMP: 2000psig @ 100°F, MOUNTED ON 6" BRIDLES, 12.625" VISIBLE GLASS, 17.625" MIN. CENTERS																																																																																																																																																																																																																				
LG-1658-02a			LEVEL GAUGE, 019R20 RELEX SIGHT GLASS, MAMP: 2000psig @ 100°F, MOUNTED ON 6" BRIDLES, 12.625" VISIBLE GLASS, 17.625" MIN. CENTERS																																																																																																																																																																																																																				
LG-1658-04	1	QUALITY	LEVEL GAUGE, 015R20 REFLEX SIGHT GLASS, MAMP: 1500psig @ 100°F, MOUNTED IN LIQUID/GAS INTERFACE, c/w (1) SET OF 0146 GAUGE VALVES, NACE MR0175-2002																																																																																																																																																																																																																				
LI-1658-05	1	PLAINSMAN	METHANOL LEVEL GAUGE, P5700-52-48-CTM, MAMP: 140psig, ½" NPT CONNECTIONS, 4'-0" LONG, METRIC HEIGHT/RATE																																																																																																																																																																																																																				
EBDV-1658-07	1	FISHER	D4 CONTROL VALVE 1" NPT, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi																																																																																																																																																																																																																				
EBDV-1658-06	1	FISHER	D4 CONTROL VALVE 1" 1500# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi																																																																																																																																																																																																																				
LG-1658-01b,c	3	QUALITY	LEVEL GAUGE, 019R20 TRANSPARENT SIGHT GLASS, MAMP: 2000psig @ 100°F, MOUNTED ON 6" BRIDLES, 12.625" VISIBLE GLASS, 17.625" MIN. CENTERS																																																																																																																																																																																																																				
TAG	QTY	MAKE	DESCRIPTION																																																																																																																																																																																																																				
PSV-1658-01	1	FARRIS	PRESSURE SAFETY VALVE, MODEL 26KA12-120 3" 300# RF x 4" 150# RF, 1" ORIFICE, SOUR PRESSURE SERVICE TRIM, SET @ 720psig																																																																																																																																																																																																																				
PSV-1658-02	2	SWAGelok	PRESSURE SAFETY VALVE, SS4R-3A5, ½" MNPT INLET x ¼" FNPT OUTLET, 316SS BODY, SET @ 720psig, MOUNTED ON METHANOL PUMPS																																																																																																																																																																																																																				
PSV-1658-04	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 2" NPT INLET x 2" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 1440psig																																																																																																																																																																																																																				
PSV-1658-05	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 1" NPT INLET x 1" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 150psig																																																																																																																																																																																																																				
LSHH-1658-01	4	MURPHY	ELECTRIC LEVEL SWITCH, LS200S5, 2" MNPT, NACE, 3116SS BODY, RATED FOR 2000psi, 304SS FLOAT @ 0.5 SG, SPDT SNAP ACTING, CLASS 1 DIV 1																																																																																																																																																																																																																				
LSLL-1658-01			LSLL-1658-01																																																																																																																																																																																																																				
LSLL-1658-02			LSLL-1658-02																																																																																																																																																																																																																				
LSHH-1658-04			LSHH-1658-04																																																																																																																																																																																																																				
PT-1658-01	4	ROSEMOUNT	ROSEMOUNT 2088 PRESSURE TRANSMITTER P/n. 208863522A1B4C6																																																																																																																																																																																																																				
PT-1658-02/03			PT-1658-02/03																																																																																																																																																																																																																				
PT-1658-04			PT-1658-04																																																																																																																																																																																																																				
ESDV-1658-01	3	NUTRON	BALL VALVE, 3" 300#, FLOATER STYLE RF RP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC MODEL: ES0350.02D04A.27K2																																																																																																																																																																																																																				
ESDV-1658-02			ESDV-1658-02																																																																																																																																																																																																																				
ESDV-1658-05			ESDV-1658-05																																																																																																																																																																																																																				
EBDV-1658-04	1	FISHER	D4 CONTROL VALVE 1" 300# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi																																																																																																																																																																																																																				
EBDV-1658-03	1	FISHER	D4 CONTROL VALVE 1" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi																																																																																																																																																																																																																				
PV-1658-01	1	CVS CONTROLS	667-4-70 "EW" 12"x8" 600# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SOUR PROCESS, SIZE 70 ACTUATOR, NACE SERVICE, 6-30psi SUPPLY, ATO/FC																																																																																																																																																																																																																				
PV-1658-01			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE																																																																																																																																																																																																																				
PV-1658-03	1	CVS CONTROLS	CONTROL VALVE: 667-4-70 "EW" 12"x8" 300# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SIZE 70 ACTUATOR, 6-30psi SUPPLY, ATO/FC, BOTH NACE SERVICE																																																																																																																																																																																																																				
PV-1658-03			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE																																																																																																																																																																																																																				
ESDV-1658-08	1	NUTRON	BALL VALVE, 2" 600#, FLOATER STYLE RF FP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC																																																																																																																																																																																																																				
LV-1658-01	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE																																																																																																																																																																																																																				
LV-1658-02	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 1" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE																																																																																																																																																																																																																				
LV-1658-03	1	FISHER	D2 FLOPRO LIQUID CONTROL VALVE, 1" FNPT END CONNECTIONS, STANDARD NACE SERVICE, 3-15psi SUPPLY, AIR TO OPEN/FC, RATED: 2250psi @ 200°F																																																																																																																																																																																																																				
LY-1658-01	2	FISHER	I2P-100 TRANSDUCER, 4-20mA INPUT, 2-33psi FIELD SELECTABLE OUTPUT, FACTORY APPROVED, CSA APPROVED, X-PROOF, CLASS 1 DIV. 1,																																																																																																																																																																																																																				
LY-1658-02			LY-1658-02																																																																																																																																																																																																																				
LC-1658-03	1	FISHER	L2 LIQUID LEVEL CONTROLLER, 2" NPT PROCESS CONNECTION, STANDARD NACE SERVICE, SNAP ACTING CONTROL, DIRECT ACTING INSTRUMENT SIGNAL, 35psi SUPPLY, PNEUMATIC																																																																																																																																																																																																																				
ESDV-1658-01	4	ASCO	EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF, MOP: 115psig																																																																																																																																																																																																																				
EBDV-1658-03	4	ASCO	EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF																																																																																																																																																																																																																				
FE-1658-01	1	DANIEL	12" 300# SCH. 80 SENIOR METER RUN, NACE PROCESS, 224" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT																																																																																																																																																																																																																				
FE-1658-02	1	DANIEL	6" 900# SCH. 160 SENIOR METER RUN, NACE PROCESS, 118" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT																																																																																																																																																																																																																				
FE-1658-05	1	DANIEL	2" 600# SCH. 80 SENIOR METER RUN, NACE PROCESS, 48" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT																																																																																																																																																																																																																				
7 <table> <tr> <th>TAG</th><th>QTY</th><th>MAKE</th><th>DESCRIPTION</th></tr> <tr> <td>PSV-1658-02</td><td>2</td><td>SWAGelok</td><td>PRESSURE SAFETY VALVE, SS4R-3A5, ½" MNPT INLET x ¼" FNPT OUTLET, 316SS BODY, SET @ 720psig, MOUNTED ON METHANOL PUMPS</td></tr> <tr> <td>PSV-1658-03</td><td></td><td></td><td>PSV-1658-03</td></tr> <tr> <td>PSV-1658-04</td><td>1</td><td>MERCER</td><td>PRESSURE SAFETY VALVE, MODEL 9100, 2" NPT INLET x 2" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 1440psig</td></tr> <tr> <td>PSV-1658-05</td><td>1</td><td>MERCER</td><td>PRESSURE SAFETY VALVE, MODEL 9100, 1" NPT INLET x 1" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 150psig</td></tr> <tr> <td>LSHH-1658-01</td><td>4</td><td>MURPHY</td><td>ELECTRIC LEVEL SWITCH, LS200S5, 2" MNPT, NACE, 3116SS BODY, RATED FOR 2000psi, 304SS FLOAT @ 0.5 SG, SPDT SNAP ACTING, CLASS 1 DIV 1</td></tr> <tr> <td>LSLL-1658-01</td><td></td><td></td><td>LSLL-1658-01</td></tr> <tr> <td>LSLL-1658-02</td><td></td><td></td><td>LSLL-1658-02</td></tr> <tr> <td>LSHH-1658-04</td><td></td><td></td><td>LSHH-1658-04</td></tr> <tr> <td>PT-1658-01</td><td>4</td><td>ROSEMOUNT</td><td>ROSEMOUNT 2088 PRESSURE TRANSMITTER P/n. 208863522A1B4C6</td></tr> <tr> <td>PT-1658-02/03</td><td></td><td></td><td>PT-1658-02/03</td></tr> <tr> <td>PT-1658-04</td><td></td><td></td><td>PT-1658-04</td></tr> <tr> <td>ESDV-1658-01</td><td>3</td><td>NUTRON</td><td>BALL VALVE, 3" 300#, FLOATER STYLE RF RP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC MODEL: ES0350.02D04A.27K2</td></tr> <tr> <td>ESDV-1658-02</td><td></td><td></td><td>ESDV-1658-02</td></tr> <tr> <td>ESDV-1658-05</td><td></td><td></td><td>ESDV-1658-05</td></tr> <tr> <td>EBDV-1658-04</td><td>1</td><td>FISHER</td><td>D4 CONTROL VALVE 1" 300# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi</td></tr> <tr> <td>EBDV-1658-03</td><td>1</td><td>FISHER</td><td>D4 CONTROL VALVE 1" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi</td></tr> <tr> <td>PV-1658-01</td><td>1</td><td>CVS CONTROLS</td><td>667-4-70 "EW" 12"x8" 600# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SOUR PROCESS, SIZE 70 ACTUATOR, NACE SERVICE, 6-30psi SUPPLY, ATO/FC</td></tr> <tr> <td>PV-1658-01</td><td></td><td></td><td>c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE</td></tr> <tr> <td>PV-1658-03</td><td>1</td><td>CVS CONTROLS</td><td>CONTROL VALVE: 667-4-70 "EW" 12"x8" 300# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SIZE 70 ACTUATOR, 6-30psi SUPPLY, ATO/FC, BOTH NACE SERVICE</td></tr> <tr> <td>PV-1658-03</td><td></td><td></td><td>c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE</td></tr> <tr> <td>ESDV-1658-08</td><td>1</td><td>NUTRON</td><td>BALL VALVE, 2" 600#, FLOATER STYLE RF FP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC</td></tr> <tr> <td>LV-1658-01</td><td>1</td><td>FISHER</td><td>D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE</td></tr> <tr> <td>LV-1658-02</td><td>1</td><td>FISHER</td><td>D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 1" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE</td></tr> <tr> <td>LV-1658-03</td><td>1</td><td>FISHER</td><td>D2 FLOPRO LIQUID CONTROL VALVE, 1" FNPT END CONNECTIONS, STANDARD NACE SERVICE, 3-15psi SUPPLY, AIR TO OPEN/FC, RATED: 2250psi @ 200°F</td></tr> <tr> <td>LY-1658-01</td><td>2</td><td>FISHER</td><td>I2P-100 TRANSDUCER, 4-20mA INPUT, 2-33psi FIELD SELECTABLE OUTPUT, FACTORY APPROVED, CSA APPROVED, X-PROOF, CLASS 1 DIV. 1,</td></tr> <tr> <td>LY-1658-02</td><td></td><td></td><td>LY-1658-02</td></tr> <tr> <td>LC-1658-03</td><td>1</td><td>FISHER</td><td>L2 LIQUID LEVEL CONTROLLER, 2" NPT PROCESS CONNECTION, STANDARD NACE SERVICE, SNAP ACTING CONTROL, DIRECT ACTING INSTRUMENT SIGNAL, 35psi SUPPLY, PNEUMATIC</td></tr> <tr> <td>ESDV-1658-01</td><td>4</td><td>ASCO</td><td>EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF, MOP: 115psig</td></tr> <tr> <td>EBDV-1658-03</td><td>4</td><td>ASCO</td><td>EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF</td></tr> <tr> <td>FE-1658-01</td><td>1</td><td>DANIEL</td><td>12" 300# SCH. 80 SENIOR METER RUN, NACE PROCESS, 224" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT</td></tr> <tr> <td>FE-1658-02</td><td>1</td><td>DANIEL</td><td>6" 900# SCH. 160 SENIOR METER RUN, NACE PROCESS, 118" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT</td></tr> <tr> <td>FE-1658-05</td><td>1</td><td>DANIEL</td><td>2" 600# SCH. 80 SENIOR METER RUN, NACE PROCESS, 48" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT</td></tr> </table>				TAG	QTY	MAKE	DESCRIPTION	PSV-1658-02	2	SWAGelok	PRESSURE SAFETY VALVE, SS4R-3A5, ½" MNPT INLET x ¼" FNPT OUTLET, 316SS BODY, SET @ 720psig, MOUNTED ON METHANOL PUMPS	PSV-1658-03			PSV-1658-03	PSV-1658-04	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 2" NPT INLET x 2" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 1440psig	PSV-1658-05	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 1" NPT INLET x 1" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 150psig	LSHH-1658-01	4	MURPHY	ELECTRIC LEVEL SWITCH, LS200S5, 2" MNPT, NACE, 3116SS BODY, RATED FOR 2000psi, 304SS FLOAT @ 0.5 SG, SPDT SNAP ACTING, CLASS 1 DIV 1	LSLL-1658-01			LSLL-1658-01	LSLL-1658-02			LSLL-1658-02	LSHH-1658-04			LSHH-1658-04	PT-1658-01	4	ROSEMOUNT	ROSEMOUNT 2088 PRESSURE TRANSMITTER P/n. 208863522A1B4C6	PT-1658-02/03			PT-1658-02/03	PT-1658-04			PT-1658-04	ESDV-1658-01	3	NUTRON	BALL VALVE, 3" 300#, FLOATER STYLE RF RP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC MODEL: ES0350.02D04A.27K2	ESDV-1658-02			ESDV-1658-02	ESDV-1658-05			ESDV-1658-05	EBDV-1658-04	1	FISHER	D4 CONTROL VALVE 1" 300# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi	EBDV-1658-03	1	FISHER	D4 CONTROL VALVE 1" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi	PV-1658-01	1	CVS CONTROLS	667-4-70 "EW" 12"x8" 600# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SOUR PROCESS, SIZE 70 ACTUATOR, NACE SERVICE, 6-30psi SUPPLY, ATO/FC	PV-1658-01			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE	PV-1658-03	1	CVS CONTROLS	CONTROL VALVE: 667-4-70 "EW" 12"x8" 300# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SIZE 70 ACTUATOR, 6-30psi SUPPLY, ATO/FC, BOTH NACE SERVICE	PV-1658-03			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE	ESDV-1658-08	1	NUTRON	BALL VALVE, 2" 600#, FLOATER STYLE RF FP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC	LV-1658-01	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE	LV-1658-02	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 1" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE	LV-1658-03	1	FISHER	D2 FLOPRO LIQUID CONTROL VALVE, 1" FNPT END CONNECTIONS, STANDARD NACE SERVICE, 3-15psi SUPPLY, AIR TO OPEN/FC, RATED: 2250psi @ 200°F	LY-1658-01	2	FISHER	I2P-100 TRANSDUCER, 4-20mA INPUT, 2-33psi FIELD SELECTABLE OUTPUT, FACTORY APPROVED, CSA APPROVED, X-PROOF, CLASS 1 DIV. 1,	LY-1658-02			LY-1658-02	LC-1658-03	1	FISHER	L2 LIQUID LEVEL CONTROLLER, 2" NPT PROCESS CONNECTION, STANDARD NACE SERVICE, SNAP ACTING CONTROL, DIRECT ACTING INSTRUMENT SIGNAL, 35psi SUPPLY, PNEUMATIC	ESDV-1658-01	4	ASCO	EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF, MOP: 115psig	EBDV-1658-03	4	ASCO	EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF	FE-1658-01	1	DANIEL	12" 300# SCH. 80 SENIOR METER RUN, NACE PROCESS, 224" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT	FE-1658-02	1	DANIEL	6" 900# SCH. 160 SENIOR METER RUN, NACE PROCESS, 118" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT	FE-1658-05	1	DANIEL	2" 600# SCH. 80 SENIOR METER RUN, NACE PROCESS, 48" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT																																																																																
TAG	QTY	MAKE	DESCRIPTION																																																																																																																																																																																																																				
PSV-1658-02	2	SWAGelok	PRESSURE SAFETY VALVE, SS4R-3A5, ½" MNPT INLET x ¼" FNPT OUTLET, 316SS BODY, SET @ 720psig, MOUNTED ON METHANOL PUMPS																																																																																																																																																																																																																				
PSV-1658-03			PSV-1658-03																																																																																																																																																																																																																				
PSV-1658-04	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 2" NPT INLET x 2" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 1440psig																																																																																																																																																																																																																				
PSV-1658-05	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 1" NPT INLET x 1" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 150psig																																																																																																																																																																																																																				
LSHH-1658-01	4	MURPHY	ELECTRIC LEVEL SWITCH, LS200S5, 2" MNPT, NACE, 3116SS BODY, RATED FOR 2000psi, 304SS FLOAT @ 0.5 SG, SPDT SNAP ACTING, CLASS 1 DIV 1																																																																																																																																																																																																																				
LSLL-1658-01			LSLL-1658-01																																																																																																																																																																																																																				
LSLL-1658-02			LSLL-1658-02																																																																																																																																																																																																																				
LSHH-1658-04			LSHH-1658-04																																																																																																																																																																																																																				
PT-1658-01	4	ROSEMOUNT	ROSEMOUNT 2088 PRESSURE TRANSMITTER P/n. 208863522A1B4C6																																																																																																																																																																																																																				
PT-1658-02/03			PT-1658-02/03																																																																																																																																																																																																																				
PT-1658-04			PT-1658-04																																																																																																																																																																																																																				
ESDV-1658-01	3	NUTRON	BALL VALVE, 3" 300#, FLOATER STYLE RF RP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC MODEL: ES0350.02D04A.27K2																																																																																																																																																																																																																				
ESDV-1658-02			ESDV-1658-02																																																																																																																																																																																																																				
ESDV-1658-05			ESDV-1658-05																																																																																																																																																																																																																				
EBDV-1658-04	1	FISHER	D4 CONTROL VALVE 1" 300# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi																																																																																																																																																																																																																				
EBDV-1658-03	1	FISHER	D4 CONTROL VALVE 1" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi																																																																																																																																																																																																																				
PV-1658-01	1	CVS CONTROLS	667-4-70 "EW" 12"x8" 600# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SOUR PROCESS, SIZE 70 ACTUATOR, NACE SERVICE, 6-30psi SUPPLY, ATO/FC																																																																																																																																																																																																																				
PV-1658-01			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE																																																																																																																																																																																																																				
PV-1658-03	1	CVS CONTROLS	CONTROL VALVE: 667-4-70 "EW" 12"x8" 300# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SIZE 70 ACTUATOR, 6-30psi SUPPLY, ATO/FC, BOTH NACE SERVICE																																																																																																																																																																																																																				
PV-1658-03			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE																																																																																																																																																																																																																				
ESDV-1658-08	1	NUTRON	BALL VALVE, 2" 600#, FLOATER STYLE RF FP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC																																																																																																																																																																																																																				
LV-1658-01	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE																																																																																																																																																																																																																				
LV-1658-02	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 1" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE																																																																																																																																																																																																																				
LV-1658-03	1	FISHER	D2 FLOPRO LIQUID CONTROL VALVE, 1" FNPT END CONNECTIONS, STANDARD NACE SERVICE, 3-15psi SUPPLY, AIR TO OPEN/FC, RATED: 2250psi @ 200°F																																																																																																																																																																																																																				
LY-1658-01	2	FISHER	I2P-100 TRANSDUCER, 4-20mA INPUT, 2-33psi FIELD SELECTABLE OUTPUT, FACTORY APPROVED, CSA APPROVED, X-PROOF, CLASS 1 DIV. 1,																																																																																																																																																																																																																				
LY-1658-02			LY-1658-02																																																																																																																																																																																																																				
LC-1658-03	1	FISHER	L2 LIQUID LEVEL CONTROLLER, 2" NPT PROCESS CONNECTION, STANDARD NACE SERVICE, SNAP ACTING CONTROL, DIRECT ACTING INSTRUMENT SIGNAL, 35psi SUPPLY, PNEUMATIC																																																																																																																																																																																																																				
ESDV-1658-01	4	ASCO	EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF, MOP: 115psig																																																																																																																																																																																																																				
EBDV-1658-03	4	ASCO	EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF																																																																																																																																																																																																																				
FE-1658-01	1	DANIEL	12" 300# SCH. 80 SENIOR METER RUN, NACE PROCESS, 224" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT																																																																																																																																																																																																																				
FE-1658-02	1	DANIEL	6" 900# SCH. 160 SENIOR METER RUN, NACE PROCESS, 118" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT																																																																																																																																																																																																																				
FE-1658-05	1	DANIEL	2" 600# SCH. 80 SENIOR METER RUN, NACE PROCESS, 48" OAL, FLOW CONDITIONER, BUILT TO AGA 2000, 100% X-RAY, PWHT																																																																																																																																																																																																																				
3 <table> <tr> <th>TAG</th><th>QTY</th><th>MAKE</th><th>DESCRIPTION</th></tr> <tr> <td>PSV-1658-02</td><td>2</td><td>SWAGelok</td><td>PRESSURE SAFETY VALVE, SS4R-3A5, ½" MNPT INLET x ¼" FNPT OUTLET, 316SS BODY, SET @ 720psig, MOUNTED ON METHANOL PUMPS</td></tr> <tr> <td>PSV-1658-03</td><td></td><td></td><td>PSV-1658-03</td></tr> <tr> <td>PSV-1658-04</td><td>1</td><td>MERCER</td><td>PRESSURE SAFETY VALVE, MODEL 9100, 2" NPT INLET x 2" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 1440psig</td></tr> <tr> <td>PSV-1658-05</td><td>1</td><td>MERCER</td><td>PRESSURE SAFETY VALVE, MODEL 9100, 1" NPT INLET x 1" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 150psig</td></tr> <tr> <td>LSHH-1658-01</td><td>4</td><td>MURPHY</td><td>ELECTRIC LEVEL SWITCH, LS200S5, 2" MNPT, NACE, 3116SS BODY, RATED FOR 2000psi, 304SS FLOAT @ 0.5 SG, SPDT SNAP ACTING, CLASS 1 DIV 1</td></tr> <tr> <td>LSLL-1658-01</td><td></td><td></td><td>LSLL-1658-01</td></tr> <tr> <td>LSLL-1658-02</td><td></td><td></td><td>LSLL-1658-02</td></tr> <tr> <td>LSHH-1658-04</td><td></td><td></td><td>LSHH-1658-04</td></tr> <tr> <td>PT-1658-01</td><td>4</td><td>ROSEMOUNT</td><td>ROSEMOUNT 2088 PRESSURE TRANSMITTER P/n. 208863522A1B4C6</td></tr> <tr> <td>PT-1658-02/03</td><td></td><td></td><td>PT-1658-02/03</td></tr> <tr> <td>PT-1658-04</td><td></td><td></td><td>PT-1658-04</td></tr> <tr> <td>ESDV-1658-01</td><td>3</td><td>NUTRON</td><td>BALL VALVE, 3" 300#, FLOATER STYLE RF RP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC MODEL: ES0350.02D04A.27K2</td></tr> <tr> <td>ESDV-1658-02</td><td></td><td></td><td>ESDV-1658-02</td></tr> <tr> <td>ESDV-1658-05</td><td></td><td></td><td>ESDV-1658-05</td></tr> <tr> <td>EBDV-1658-04</td><td>1</td><td>FISHER</td><td>D4 CONTROL VALVE 1" 300# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi</td></tr> <tr> <td>EBDV-1658-03</td><td>1</td><td>FISHER</td><td>D4 CONTROL VALVE 1" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi</td></tr> <tr> <td>PV-1658-01</td><td>1</td><td>CVS CONTROLS</td><td>667-4-70 "EW" 12"x8" 600# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SOUR PROCESS, SIZE 70 ACTUATOR, NACE SERVICE, 6-30psi SUPPLY, ATO/FC</td></tr> <tr> <td>PV-1658-01</td><td></td><td></td><td>c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE</td></tr> <tr> <td>PV-1658-03</td><td>1</td><td>CVS CONTROLS</td><td>CONTROL VALVE: 667-4-70 "EW" 12"x8" 300# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SIZE 70 ACTUATOR, 6-30psi SUPPLY, ATO/FC, BOTH NACE SERVICE</td></tr> <tr> <td>PV-1658-03</td><td></td><td></td><td>c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE</td></tr> <tr> <td>ESDV-1658-08</td><td>1</td><td>NUTRON</td><td>BALL VALVE, 2" 600#, FLOATER STYLE RF FP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC</td></tr> <tr> <td>LV-1658-01</td><td>1</td><td>FISHER</td><td>D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE</td></tr> <tr> <td>LV-1658-02</td><td>1</td><td>FISHER</td><td>D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 1" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE</td></tr> <tr> <td>LV-1658-03</td><td>1</td><td>FISHER</td><td>D2 FLOPRO LIQUID CONTROL VALVE, 1" FNPT END CONNECTIONS, STANDARD NACE SERVICE, 3-15psi SUPPLY, AIR TO OPEN/FC, RATED: 2250psi @ 200°F</td></tr> <tr> <td>LY-1658-01</td><td>2</td><td>FISHER</td><td>I2P-100 TRANSDUCER, 4-20mA INPUT, 2-33psi FIELD SELECTABLE OUTPUT, FACTORY APPROVED, CSA APPROVED, X-PROOF, CLASS 1 DIV. 1,</td></tr> <tr> <td>LY-1658-02</td><td></td><td></td><td>LY-1658-02</td></tr> <tr> <td>LC-1658-03</td><td>1</td><td>FISHER</td><td>L2 LIQUID LEVEL CONTROLLER, 2" NPT PROCESS CONNECTION, STANDARD NACE SERVICE, SNAP ACTING CONTROL, DIRECT ACTING INSTRUMENT SIGNAL, 35psi SUPPLY, PNEUMATIC</td></tr> <tr> <td>ESDV-1658-01</td><td>4</td><td>ASCO</td><td>EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF, MOP: 115psig</td></tr></table>	TAG	QTY	MAKE	DESCRIPTION	PSV-1658-02	2	SWAGelok	PRESSURE SAFETY VALVE, SS4R-3A5, ½" MNPT INLET x ¼" FNPT OUTLET, 316SS BODY, SET @ 720psig, MOUNTED ON METHANOL PUMPS	PSV-1658-03			PSV-1658-03	PSV-1658-04	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 2" NPT INLET x 2" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 1440psig	PSV-1658-05	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 1" NPT INLET x 1" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 150psig	LSHH-1658-01	4	MURPHY	ELECTRIC LEVEL SWITCH, LS200S5, 2" MNPT, NACE, 3116SS BODY, RATED FOR 2000psi, 304SS FLOAT @ 0.5 SG, SPDT SNAP ACTING, CLASS 1 DIV 1	LSLL-1658-01			LSLL-1658-01	LSLL-1658-02			LSLL-1658-02	LSHH-1658-04			LSHH-1658-04	PT-1658-01	4	ROSEMOUNT	ROSEMOUNT 2088 PRESSURE TRANSMITTER P/n. 208863522A1B4C6	PT-1658-02/03			PT-1658-02/03	PT-1658-04			PT-1658-04	ESDV-1658-01	3	NUTRON	BALL VALVE, 3" 300#, FLOATER STYLE RF RP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC MODEL: ES0350.02D04A.27K2	ESDV-1658-02			ESDV-1658-02	ESDV-1658-05			ESDV-1658-05	EBDV-1658-04	1	FISHER	D4 CONTROL VALVE 1" 300# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi	EBDV-1658-03	1	FISHER	D4 CONTROL VALVE 1" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi	PV-1658-01	1	CVS CONTROLS	667-4-70 "EW" 12"x8" 600# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SOUR PROCESS, SIZE 70 ACTUATOR, NACE SERVICE, 6-30psi SUPPLY, ATO/FC	PV-1658-01			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE	PV-1658-03	1	CVS CONTROLS	CONTROL VALVE: 667-4-70 "EW" 12"x8" 300# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SIZE 70 ACTUATOR, 6-30psi SUPPLY, ATO/FC, BOTH NACE SERVICE	PV-1658-03			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE	ESDV-1658-08	1	NUTRON	BALL VALVE, 2" 600#, FLOATER STYLE RF FP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC	LV-1658-01	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE	LV-1658-02	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 1" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE	LV-1658-03	1	FISHER	D2 FLOPRO LIQUID CONTROL VALVE, 1" FNPT END CONNECTIONS, STANDARD NACE SERVICE, 3-15psi SUPPLY, AIR TO OPEN/FC, RATED: 2250psi @ 200°F	LY-1658-01	2	FISHER	I2P-100 TRANSDUCER, 4-20mA INPUT, 2-33psi FIELD SELECTABLE OUTPUT, FACTORY APPROVED, CSA APPROVED, X-PROOF, CLASS 1 DIV. 1,	LY-1658-02			LY-1658-02	LC-1658-03	1	FISHER	L2 LIQUID LEVEL CONTROLLER, 2" NPT PROCESS CONNECTION, STANDARD NACE SERVICE, SNAP ACTING CONTROL, DIRECT ACTING INSTRUMENT SIGNAL, 35psi SUPPLY, PNEUMATIC	ESDV-1658-01	4	ASCO	EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF, MOP: 115psig																																																																																																			
TAG	QTY	MAKE	DESCRIPTION																																																																																																																																																																																																																				
PSV-1658-02	2	SWAGelok	PRESSURE SAFETY VALVE, SS4R-3A5, ½" MNPT INLET x ¼" FNPT OUTLET, 316SS BODY, SET @ 720psig, MOUNTED ON METHANOL PUMPS																																																																																																																																																																																																																				
PSV-1658-03			PSV-1658-03																																																																																																																																																																																																																				
PSV-1658-04	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 2" NPT INLET x 2" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 1440psig																																																																																																																																																																																																																				
PSV-1658-05	1	MERCER	PRESSURE SAFETY VALVE, MODEL 9100, 1" NPT INLET x 1" NPT OUTLET, STD. PRESSURE SERVICE TRIM, WCB BODY, SET @ 150psig																																																																																																																																																																																																																				
LSHH-1658-01	4	MURPHY	ELECTRIC LEVEL SWITCH, LS200S5, 2" MNPT, NACE, 3116SS BODY, RATED FOR 2000psi, 304SS FLOAT @ 0.5 SG, SPDT SNAP ACTING, CLASS 1 DIV 1																																																																																																																																																																																																																				
LSLL-1658-01			LSLL-1658-01																																																																																																																																																																																																																				
LSLL-1658-02			LSLL-1658-02																																																																																																																																																																																																																				
LSHH-1658-04			LSHH-1658-04																																																																																																																																																																																																																				
PT-1658-01	4	ROSEMOUNT	ROSEMOUNT 2088 PRESSURE TRANSMITTER P/n. 208863522A1B4C6																																																																																																																																																																																																																				
PT-1658-02/03			PT-1658-02/03																																																																																																																																																																																																																				
PT-1658-04			PT-1658-04																																																																																																																																																																																																																				
ESDV-1658-01	3	NUTRON	BALL VALVE, 3" 300#, FLOATER STYLE RF RP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC MODEL: ES0350.02D04A.27K2																																																																																																																																																																																																																				
ESDV-1658-02			ESDV-1658-02																																																																																																																																																																																																																				
ESDV-1658-05			ESDV-1658-05																																																																																																																																																																																																																				
EBDV-1658-04	1	FISHER	D4 CONTROL VALVE 1" 300# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi																																																																																																																																																																																																																				
EBDV-1658-03	1	FISHER	D4 CONTROL VALVE 1" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" SST TRIM, c/w SIZE 40 ACTUATOR, FAIL OPEN, NACE, 0-33 psi																																																																																																																																																																																																																				
PV-1658-01	1	CVS CONTROLS	667-4-70 "EW" 12"x8" 600# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SOUR PROCESS, SIZE 70 ACTUATOR, NACE SERVICE, 6-30psi SUPPLY, ATO/FC																																																																																																																																																																																																																				
PV-1658-01			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE																																																																																																																																																																																																																				
PV-1658-03	1	CVS CONTROLS	CONTROL VALVE: 667-4-70 "EW" 12"x8" 300# RF CONNECTIONS, LCC STEEL BODY, 17-4 PH CAGE, 316 SST PLUG & SEAT, LCC BODY TFE PACKING, SIZE 70 ACTUATOR, 6-30psi SUPPLY, ATO/FC, BOTH NACE SERVICE																																																																																																																																																																																																																				
PV-1658-03			c/w CVS SERIES, YT-2400L ELECTRO-PNEUMATIC SMART VALVE POSITIONER, 4-20mA INPUT, 6-30psi OUTPUT, HART COMPATIBLE																																																																																																																																																																																																																				
ESDV-1658-08	1	NUTRON	BALL VALVE, 2" 600#, FLOATER STYLE RF FP, A350-LF2 BODY, ACTUATOR: PNEUMATIC, RACK & PINION, SPRING RETURN, FAIL OPEN, 80psi SWEET SUPPLY, SOUR PROCESS, EL-O-MATIC																																																																																																																																																																																																																				
LV-1658-01	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 3/4" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE																																																																																																																																																																																																																				
LV-1658-02	1	FISHER	D3 CONTROL VALVE 2" 600# RF, LCC BODY, NACE PLUG 316 SST/17-4 SEAT RING, 1" FLOPRO TRIM, INTEGRAL ACTUATOR, FAIL CLOSE, NACE SERVICE																																																																																																																																																																																																																				
LV-1658-03	1	FISHER	D2 FLOPRO LIQUID CONTROL VALVE, 1" FNPT END CONNECTIONS, STANDARD NACE SERVICE, 3-15psi SUPPLY, AIR TO OPEN/FC, RATED: 2250psi @ 200°F																																																																																																																																																																																																																				
LY-1658-01	2	FISHER	I2P-100 TRANSDUCER, 4-20mA INPUT, 2-33psi FIELD SELECTABLE OUTPUT, FACTORY APPROVED, CSA APPROVED, X-PROOF, CLASS 1 DIV. 1,																																																																																																																																																																																																																				
LY-1658-02			LY-1658-02																																																																																																																																																																																																																				
LC-1658-03	1	FISHER	L2 LIQUID LEVEL CONTROLLER, 2" NPT PROCESS CONNECTION, STANDARD NACE SERVICE, SNAP ACTING CONTROL, DIRECT ACTING INSTRUMENT SIGNAL, 35psi SUPPLY, PNEUMATIC																																																																																																																																																																																																																				
ESDV-1658-01	4	ASCO	EF83200202-24, 3 WAY SOLENOID VALVE, ¼" FNPT CONNECTIONS, 303 SST BODY, 24VDC COIL, CSA APPROVED, X-PROOF, MOP: 115psig																																																																																																																																																																																																																				