66173028



FORM U-1A MANUFACTURER'S DATA REPORT FOR PRESSURE VESSELS (Alternative Form for Single Chamber, Completely Shop or Field Fabricated Vessels Only) As Required by the Provisions of the ASME Boiler and Pressure Vessel Code Rules, Section VIII, Division 1

Manufactured and certified by											
3. Location of installation 4. Type Vertical 31834213 (Name and address) (V2134.213 31833-V0404 Rev.4 2010 (Vear built) 5. The chemical and physical properties of all parts meet the requirements of material specifications of the ASME BOILER AND PRESSURE VESSEL CODE. The design, construction, and workmanship conform to ASME Rules, Section VIII, Division 1 2007 Vear Unit) 6. Shell: SA-106B 0.593" (Code Case numbers) (Special service per UG-120(st)) 7. Seams: Seamless Pipe											
4. Type Vertical 31834213 V2134.213 31833-V0404 Rev.4 — 2010											
Commonstrated or various, Lank Manufacturer's serial Number CRN Covaring Number (National Board number) (Year built)											
CODE. The design, construction, and workmanship conform to ASME Rules, Section VIII, Division 1 Code Case numbers Code Case number											
to 2009 (Addenda (date)) (Ad											
Code Case numbers Code Case number Code											
Material spec, number, grade Seamless Pipe											
R. Heads: (a) Material SA-516-70N Sandius Sandiu											
8. Heads: (a) Material SA-516-70N (b) Material SA-516-70N (Spec. no., grade) Location (Top, Bottom, Ends) Thickness Allowance Radius Radius Ratio Apex Angle Radius Diameter (Convex or Concave)											
Coation (Top, Bottom, Ends) Corrosion Crown Radius Diameter (Convex or Concave)											
Concave Concave Radius Diameter (Convex or Concave)											
(a) Top 0.4375" 0.0625" SE 2:1 Concave (b) Bottom 0.4375" 0.0625" SE 2:1 Concave If removable, bolts used (describe other fastenings) 9. MAWP 655 PSIG (Internet) (External) Min. design metal temp20°F at 655 PSIG . Hydro., pneu., or comb. test pressure 852 PSIG Proof Test Material Spec. number, grade, size, number) 10. Nozzles, inspection, and safety valve openings:											
Bottom 0.4375" 0.0625" SE 2:1 Concave											
9. MAWP 655 PSIG at max. temp. (Adaterial spec. number, grade, size, number) (Internel) (External) (Internel) (External) Min. design metal temp20°F at 655 PSIG . Hydro., pneu., or comb. test pressure 852 PSIG . Proof Test 10. Nozzles, inspection, and safety valve openings:											
9. MAWP 655 PSIG at max. temp. 300°F (Internal) (External) Min. design metal temp 20°F at 655 PSIG . Hydro., pneu., or comb. test pressure 852 PSIG Proof Test 10. Nozzles, inspection, and safety valve openings:											
Min. design metal temp esternal) Proof Test Purpose Diameter (Internal) (Internal) (External) Hydro., pneu., or comb. test pressure 852 PSIG Nozzles, inspection, and safety valve openings:											
Proof Test 10. Nozzles, inspection, and safety valve openings: Purpose 10. Diameter Time Material Nominal Reinforcement How Location											
Purpose Nominal Reinforcement How Location											
TUIDOSE AL., Diditioto Tuno Material LOCATION											
(Inlet, Outlet, Drain) Number or Size Type Induction Thickness Material Attached SEE ATTACHED U4 FORM											
11, Supports: Skirt Yes Lugs 2 Legs Other Attached Head & Welded											
(Yes or no) (Number) (Describe) (Where and how)											
items of the report:											
(Name of part, item number, Manufacturer's name and identifying stamp) Vessel Type: Stage #2 Suction Scrubber Construction Drawing: 31834-V-0404 Rev.4											
Impact testing: exempt, per UG-20(f)(1-5), UCS-66(c) Volume: 14 Cu. Ft.											
Relief Valve installed on piping in accordance with UG-125											
2 - 3" CL300 Hub Flange RF SA-105N Studs: 3/4"Ø 4 1/2" Lg. SA-193-B7 Qty. 16, Nuts: 3/4"Ø SA-194-2H Qty. 32											
1 - 1 1/2" CL300 Hub Flange RF SA-105N Studs: 3/4"Ø 4" Lg. SA-193-B7 Qty. 4, Nuts: 3/4"Ø SA-194-2H Qty. 8 2 - 2" CL300 Hub Flange RF SA-105N Studs: 5/8"Ø 4" Lg. SA-193-B7 Qty. 24, Nuts: 5/8"Ø SA-194-2H Qty. 48											
2 - 2" CL300 Hub Frange RF SA-105N Studs: 5/8"Ø 4" Lg. SA-193-B7 Qty. 16, Nuts: 5/8"Ø SA-194-2H Qty. 32											
CERTIFICATE OF SHOP/FIELD COMPLIANCE We certify that the statements made in this report are correct and that all details of design, material, construction, and workmanship of this vessel											
We certify that the statements made in this report are correct and that all details of design, material, construction, and workmanship of this vessel conform to the ASME BOILER AND PRESSURE VESSEL CODE, Section VIII, Division 1. "U" Certificate of Authorization Number 33,658											
expires November 26, 2011											
Date 22 Sept 2010 Co. name Enerflex Ltd. Signed OLUVA CM (Manufacturer) (Interpretative)											
CERTIFICATE OF SHOP/FIELD INSPECTION											
Vessel constructed by Enerflex Ltd. at Calgary, Alberta, Canada											
I, the undersigned, holding a valid commission issued by the National Board of Boiler and Pressure Vessel Inspectors and/or the State or Province of Alberta and employed by ABSA											
Alberta and employed by ABSA and state that,											
to the best of my knowledge and belief, the Manufacturer has constructed this pressure vessel in accordance with ASME BOILER AND PRESSURE											
VESSEL CODE, Section VIII, Division 1. By signing this certificate neither the Inspector nor his/her employer makes any warranty, expressed or Implied, concerning the pressure vessel described in this Manufacturer's Data Report. Furthermore, neither the Inspector nor his/her employer											
shall be liable in any manner for any personal injury of property damage or a loss of any kind arising from or connected with this inspection.											
Date SEP 2 3 7010 Signed Commissions [National Board (Incl. endorsements), State, Province and Number]											

FORM U-4 MANUFACTURER'S DATA REPORT SUPPLEMENTARY SHEET As Required by the Provisions of the ASME Boiler and Pressure Vessel Code Rules, Section VIII, Division 1

1.	Manufac	tured and certified	by		Enerflex L	td., 10121 Barlow Trail NE. C	algary. Al	berta, T3J 3C	6	
2.	Manufac	tured for		Hus	sky Oil Operat	me and address of Manufacturer) tions Ltd., Box 4490, Stn. D Ca	algary Alb	erta, T2 <u>P 3</u> G7	•	
		of Installation		110	(N	ame and address of Purchaser) CMullen TCP, LSD: 03-35- (Name and address)				
4.	Туре: _	Vertica (Horizontal, vertical, o	or sphere)		Stage #2	2 Suction Scrubber separator, heat exch., etc.)	31834213 (Manufacturers serial Number)			
-	V2134.213 (GRN)				31833-V0404 Rev.4 (National Contents of the Co					
					VIII.	Remarks				- Angel Company and Angel Comp
	ta Report	Purpose (Inlet, Outlet, Drain)	Number	Diameter or Size	Туре	Material	Nominal Thickness	Reinforcement Material	How Attached	Location
	I0-N1	Inlet	1	6"NPS	CL300 RFWN	SA-105N/SA-234-WPB/SA-106B	0.718"		UW16.1(c)	Shell
	0-N2	Outlet	1	6"NPS	CL300 RFWN	SA-105N/SA-106B	0.718"		UW16.1(c)	Shell
	10-N3	LC	1	3"NPS	CL300 RFLWN	SA-105N	0.81"	64616	UW16.1(c)	Shell
	0-N4	LS	1	3"NPS	CL300 RFLWN	SA-105N	0.81"		UW16.1(c)	Shell
1	10-N5	Drain	1	1.5"NPS	CL300 RFWN	SA-105N/SA-234-WPB/SA-106B	0.281"		UW16.1(c)	Head
1	10-N6	TI	1	2"NPS	CL300 RFWN	SA-105N/SA-106B	0.343"		UW16.1(c)	Shell
1	0-N7	Insp.	1	2"NPS	CL300 RFWN	SA-105N/SA-106B	0.343"		UW16.1(c)	Head
1	0-N8A	LG	1	2"NPS	CL300 RFWN	SA-105N/SA-106B	0.343"		UW16.1(c)	Shell
1	0-N8B	LG	1	2"NPS	CL300 RFWN	SA-105N/SA-106B	0.343"		UW16.1(c)	Shell
1	0-N10	. Pl	1	2"NPS	CL300 RFWN	SA-105N/SA-106B	0.343"		UW16.1(c)	Shell
1	0-N11	Insp.	1	2"NPS	CL300 RFWN	SA-105N/SA-106B	0.343"		UW16.1(c)	Shell
								•		
			 							
Certit	ficate of /	Authorization: Typ	ре	"U"	No	33,658 Expires	Noven	nber 26, 2011		
Date	22	Sept 2010 N	lame		Enerl	flex Ltd.	Signed		umad	<u>i</u>
Date		SEP 2 3 2010		Name	(Manufac	Qas Committoriorized (respector)	ssions	(Repti	#58	nce and Number)
					- (Auth	unican ambanasi	fienti	final allenge		