


## MODEL YS 800 CLASS 800 CARBON STEEL SCREWED / SOCKET WELD "Y" STRAINER

**DRAWING A 100** 



DESCRIPTION	MATERIAL			
BODY	ASTM A105 N			
CAP	ASTM A105 N			
GASKET	SPIRAL WOUND SS			
SCREEN	304 SS 1/32 PERF			

TEMPER	ATURE	WORK PRESS	
C	F	kPa	P.S.I.
-29 to 38	-20 to 100	13780	2000
95	200	13366	1940
150	300	13056	1895
200	400	12746	1850
260	500	11954	1735

## ALL STRAINERS ARE INDIVIDUALLY HYDROSTATICALLY TESTED TO ANSI B16.5

:	DIMENSIONS						NET		
SIZE		A		В		C		WEIGHT	
mm	in.	mm	in.	mm	in.	mm	in.	Kg.	Lbs
6	1/4	79	3 1/8	83	3 1/4	10	3/8	.9	2
10	3/8	79	3 1/8	83	3 1/4	10	3/8	.9	2
15	1/2	79	3 1/8	83	3 1/4	10	3/8	.9	2

## **FEATURES**

BODY HAS A MACHINED SEAT TO HOLD SCREEN SECURELY.

CAP HAS A MACHINED SCREEN HOLDER TO ALIGN SCREEN DURING INSTALLATION AND TO RETAIN SEDIMENT WHEN CAP IS REMOVED.

BODY IS MACHINED TO HOLD CAP GASKET IN A BLOW-OUT PROOF DESIGN.