REV.	LINE IDENTIFICATION					ORIGIN	DESTINATION	PIPE SCHEDULE	MATERIAL SPECIFICATION AND GRADE	P & I.D. DWG. NUMBER	OPERATING CONDITIONS		DESIGN CONDITIONS			TEST CONDITIONS		CORROSION ALLOWANCE (Inches)	RADIOGRAPHY (%)	POST-WELD HEAT TREATMENT	COMMENTS
	SIZE (Inches)	PIPING CLASS	COMMODITY	LINE NUMBER	INSULATION						PRESSURE (PSIG)	TEMPERATURE (°F)	PRESSURE (PSIG)	TEMPERATURE (°F)	MDMT (°F)	PRESSURE (PSIG)	TEST MEDIUM				
0	4	300	NGL	001	1½H	SKID EDGE	E-403 INLET (SS)	STD	SA-106-B	D-2011-8169-50F-001	150	10	400	500	-20	635	H20	1/16"	10%	NO	
0	4	300	NGL	002	1½H	E-403 OUTLET (SS)	SKID EDGE	STD	SA-106-B	D-2011-8169-50F-001	145	45	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	003	1H	SKID EDGE	E-401 INLET (SS)	STD	SA-106-B	D-2011-8169-50F-001	150	35	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	004	1H	E-401 OUTLET (SS)	LINE 005	STD	SA-106-B	D-2011-8169-50F-001	145	135	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	005	1H	LINE 004	T-400 INLET (N1)	STD	SA-106-B	D-2011-8169-50F-001	145	135	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	006	1H	T-400 OUTLET (N5)	E-401 INLET (TS)	STD	SA-106-B	D-2011-8169-50F-001	50	225	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	007	1H	LINE 006 / 009	LINE 009 / 011	STD	SA-106-B	D-2011-8169-50F-001	45	145	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	008	1H	LINE 007	E-403 INLET (TS)	STD	SA-106-B	D-2011-8169-50F-001	45	145	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	009	1H	E-401 OUTLET (TS)	LINE 007	STD	SA-106-B	D-2011-8169-50F-001	40	145	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	010	1H	E-403 OUTLET (TS)	LINE 011	STD	SA-106-B	D-2011-8169-50F-001	40	135	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	011	1H	LINE 007 / 010	SKID EDGE	STD	SA-106-B	D-2011-8169-50F-001	40	135	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	012		SKID EDGE	LINE 013	STD	SA-106-B	D-2011-8169-50F-001	35	120	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	013		LINE 012	SKID EDGE	STD	SA-106-B	D-2011-8169-50F-001	35	120	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	GAS	014	1H	T-400 OUTLET (N2)	LINE 015	STD	SA-106-B	D-2011-8169-50F-001	50	135	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	GAS	015	1H	LINE 014	SKID EDGE	STD	SA-106-B	D-2011-8169-50F-001	50	135	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	016	1½H	T-400 OUTLET (N3)	E-402 INLET (TS)	STD	SA-106-B	D-2011-8169-50F-001	40	175	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	017	1½H	E-402 OUTLET (TS)	T-400 INLET (N4)	STD	SA-106-B	D-2011-8169-50F-001	35	275	400	500	-20	635	H20	1/16"	10%	NO	
0	2	300	NGL	018	1½H	LINE 016	LINE 017	STD	SA-106-B	D-2011-8169-50F-001	40	175	400	500	-20	635	H20	1/16"	10%	NO	
0	2	150	FLARE	019		FLARE HEADER	SKID EDGE	STD	SA-106-B	D-2011-8169-50F-001	ATM	50	150	200	-20	225	H20	1/16"	10%	NO	
0	2	150	DRAIN	020		DRAIN HEADER	SKID EDGE	STD	SA-106-B	D-2011-8169-50F-001	ATM	50	150	200	-20	225	H20	1/16"	10%	NO	
0	2	300	NGL	021	1H	T-400 (N6)	PSV-400	STD	SA-106-B	D-2011-8169-50F-001	50	200	400	500	-20	635	H20	1/16"	10%	NO	

REVISIONS

REV.	DATE	REV. BY	DESCRIPTION
0	13-Jun-11	JM	Issued for Information

NOTES:

SEAL & PERMIT:

PROFESSIONAL ENGINEER OF ALBERTA
MASOOD A. GHORIAL

BY:	JM
DATE:	13-Jun-11
CHK'D	
CHK'D	
APP'D:	

ALCO GAS & OIL PRODUCTION EQUIPMENT LTD.

The information contained herein is the confidential property of ALCO Gas & Oil Production Equipment Ltd., and is not for publication. The information is issued on the understanding that no part thereof shall be copied or communicated to a third party without authorization in writing from ALCO Gas & Oil Production Equipment Ltd.

LINE LIST

CONDENSATE STABILIZER UNIT

CLIENT:	HUSKY OIL OPERATIONS c/o EXCELSIOR ENGINEERING	SITE:	MINEHEAD COMPRESSOR STATION (AB)
L.S.D.:	03-06-049-18 W5M	DRAWING NUMBER:	B-2011-8169-50LL-001
REVISION:	0		