



8300 Southwest 8th Street
Oklahoma City, Oklahoma

telephone: 405.787.0145 facsimile: 405.789.8188
email: info@taylorvalve.com

Date : 02-Jan-13

Serial # : 023079-106

Part#: 82G12651311

Sales Order # : 023079

Customer : R.J.V Gas Field Services

4901 Bruce Road

Vegreville AB

T9C 1C3

Customer PO # : 126101

Safety Relief Valve Certification

Taylor Valve Technology, Inc. Safety Relief Valves are designed, manufactured and tested in accordance with the provisions of the ASME Boiler and Pressure Vessel Code. as allowed for within the provisions of ASME. The published relieving capacities have been certified by the National Board of Boiler and Pressure Vessel Inspectors.

Valve Specifications

Model Number :	Taylor Model 8200 Soft Seat	Orifice :	G
Body Size :	2 Inch	Diameter:	0.775 Inches
Part Number :	82G12651311	Area :	0.472 In ²
Body Configuration :	2" MNPT X 2" FNPT	Temperature :	70 °F
Inlet Connection :		Spring Range :	1201-1600 PSIG
Outlet Connection :		Set Pressure :	1440.0 PSIG
CRN:	OG01316.2C		

Materials

Body :	WCC Carbon Steel	Spring :	17.7 PH Stainless Steel
Seat Frame :	Carbon Steel	Guide :	304 Stainless Steel
Seat Housing :	17-4 PH H900 Stainless Steel	Adj Screw :	Carbon Steel with EN Plating
Trim :	Standard	Options :	None
Seat :	FKM 90d		

Set Pressure Specifications

	ASME Units
Set Pressure :	1440.0 psig
ASME High Set Limit :	1483.2 psig
ASME Low Set Limit :	1396.8 psig

ASME (90%) rated capacity at set pressure for indicated fluid, specific gravity and temperature.

Certifying Fluid : Air 10,871 SCFM Spec Gravity : 1.00 Temp : 60 °F

Tested by :

Department : Manufacturing

Signed

Mason Buerger

Approved by :

Department : Engineering

Signed

Jay Neill

66195897


**Taylor Valve
Technology**

8300 Southwest 8th Street

Oklahoma City, Oklahoma

Serial #: 021192-210

telephone: 405.787.0145 facsimile: 405.789.8128

Date: 07-Nov-12

Part#: 82E4351311

email: info@taylorvalve.com

Sales Order #: 021192

Customer: **R.J.V. GAS FIELD SERVICES LTD**
4901 BRUCE ROAD
VEGREVILLE, AB
T9C - 1C3

Customer PO #: 125593

Safety Relief Valve Certification

Taylor Valve Technology, Inc. Safety Relief Valves are designed, manufactured and tested in accordance with the provisions of the ASME Boiler and Pressure Vessel Code, as allowed for within the provisions of ASME. The published relieving capacities have been certified by the National Board of Boiler and Pressure Vessel Inspectors.

Valve Specifications

Model Number :	Taylor Model 8200 Soft Seat	Orifice	E
Body Size :	1 Inch	Diameter:	0.620 Inches
Part Number :	82E4351311	Area :	0.212 In ²
Body Configuration :	1" MNPT X 1" FNPT	Temperature :	70 °F
Inlet Connection :		Spring Range :	101-225 PSIG
Outlet Connection :		Set Pressure :	150.0 PSIG
CRN:	0G01316.2C		

Materials

Body :	WCC Carbon Steel	Spring	17.7 PH Stainless Steel
Seat Frame :	Carbon Steel	Guide :	304 Stainless Steel
Seat Housing :	17-4 PH H900 Stainless Steel	Adj Screw :	Carbon Steel with EN Plating
Trim :	Standard	Options :	None
Seat :	FKM 90d		

Set Pressure Specifications

	ASME Units	
Set Pressure :	15.0	psig
ASME High Set Limit :	15.5	psig
ASME Low Set Limit :	14.5	psig

ASME (90%) rated capacity at set pressure for indicated fluid, specific gravity and temperature.

Certifying Fluid :	Ar	582 SCFM	Spec Gravity : 1.00	Temp : 60 °F
--------------------	----	----------	---------------------	--------------

Tested by :

Department: **Manufacturing**
 Signed [Signature]

Approved by :

Department: **Engineering**
 Signed [Signature]