



Location Name:	ANSELL		LSD:	07-27-051-19W5			
Jur #:	A0626024		Equipment/Tag No.	66197561			
<b>Equipment Description:</b>	EXCHANGER						
Manufacturer:	CALHEX INDUSTRIES						
Serial Number:	12-0779		CRN:	V9688.21			
Shell MAWP:	2758	KPA	Shell Design Temp:	70	°C		
Tube MAWP:	2758	KPA	Tube Design Temp:	73	°C		
Shell Material:	SA-333-6		Head Material:	SA-350-LF2			
Shell Thickness:	12.70	mm	Head Thickness:	69.95	mm		
<b>Corrosion Allowance:</b>	1.5875	mm	Date Built:	2012			
Size:	609.6	mm	Pipe / Rolled Plate:				
RT:	2		Streamline Report #:	STL-19-0246-DMS 1			

**NOTES:** No readings taken in 2019 for CMLs 50-55 as shown on drawing.













# **Ultrasonic Corrosion Survey**

	*All values are in millimeters unless otherwise stated.						<b>Survey Name:</b>	Husky En	ergy	Date: JUNE 16 2019		
	Streamline Report #:	STL-19-0246-DM	IS 105							Inspector: DYLA	N SUNDQUIST	
LSD: Jur #: CRN: RT:	07-27-051-19W5 A0626024 V9688.21 2	Tag Number:         66197561         V           Year Built:         2012         Se           Vessel CA:         1.588 mm         N		Location: Vessel Name: Serial Number: Manufacturer: Tube MAWP:	GAS PLAN' EXCHANG 12-0779 CALHEX IN 2758 KPA	ER	73 °C	Pipe/Plate				
CMI D	escription		Baseline				Flange ANSI:		Material:	SA-333-6		
00	SHELL	Min	<b>2014</b> 13.39	<b>2019</b> 13.46		Flag	CA 1.588	Nominal 12.700	T Min	STCR mm/yr 0.000	LTCR mm/yr 0.000	
OD: Spec:	Cylindrical 609.6 ASME VIII Div.1	Avg Comments:	13.56	13.54		11.113	1.588	12.700		Remaining Life: Retirement Date:	0.000	
	escription		Baseline				Flange ANSI:		Material:	SA-333-6		
05	SHELL		2014	2019		Flag	CA	Nominal	T Min	STCR mm/yr	LTCR mm/yr	
Shape:	Cylindrical	Min	12.80	13.21		11.113	1.588	12.700		0.000	0.000	
OD:	609.6	Avg	13.44	13.31						Remaining Life:		
Spec:	ASME VIII Div.1	Comments:								Retirement Date:		
CML De	escription		Baseline				Flange ANSI:		Material:	SA-333-6		
10	SHELL		2014	2019		Flag	CA	Nominal	T Min	STCR mm/yr	LTCR mm/yr	
Shape:	Cylindrical	Min	13.77	13.92		11.113	1.588	12.700		0.000	0.000	
OD:	609.6	Avg	14.05	14.22						Remaining Life:		
Spec:	ASME VIII Div.1	Comments:								Retirement Date:		
CML De	escription		Baseline				Flange ANSI:		Material:	SA-333-6		
15	SHELL		2014	2019		Flag	CA	Nominal	T Min	STCR mm/yr	LTCR mm/yr	
Shape:	Cylindrical	Min	13.44	13.34		11.113	1.588	12.700		0.021	0.000	
OD:	609.6	Avg	13.67	13.64						Remaining Life:		
Spec:	ASME VIII Div.1	Comments:								Retirement Date:		



#### **Ultrasonic Corrosion Survey**

Survey Name: Husky Energy **Date: JUNE 16 2019** \*All values are in millimeters unless otherwise stated. Streamline Report #: STL-19-0246-DMS 105 Inspector: DYLAN SUNDQUIST **ANSELL GAS PLANT** LSD: 07-27-051-19W5 Area: Location: Jur #: A0626024 Tag Number: 66197561 **Vessel Name: EXCHANGER** CRN: V9688.21 **Year Built:** 2012 Serial Number: 12-0779 RT: 2 **Vessel CA:** 1.588 Manufacturer: **CALHEX INDUSTRIES** mm Shell MAWP: 2758 MAWT: 70 Tube MAWP: 2758 MAWT: 73 Pipe/Plate °C °C KPA **KPA** 0 **CML Description** Baseline Flange ANSI: Material: SA-333-6 20 SHELL 2014 2019 Flag CA Nominal T Min STCR mm/yr LTCR mm/yr **Shape:** Cylindrical Min 13.41 12.88 1.588 12.700 0.106 0.000 11.113 OD: 609.6 Avg 13.56 13.11 **Remaining Life:** ASME VIII Div.1 Spec: **Comments: Retirement Date: CML** Description Flange ANSI: Material: SA-333-6 Baseline 25 SHELL 2014 2019 CA LTCR mm/yr Flag Nominal T Min STCR mm/yr **Shape:** Cylindrical Min 12.90 13.23 11.113 1.588 12.700 0.000 0.000 OD: 609.6 Avg 13.06 13.44 **Remaining Life:** Spec: ASME VIII Div.1 **Comments: Retirement Date: CML Description** Baseline Flange ANSI: Material: SA-234-WPB 30 **PIPING** 2014 2019 Flag CA Nominal T Min STCR mm/yr LTCR mm/yr **Shape:** 90° Elbow Min 7.70 7.54 7.156 1.022 8.179 0.031 0.091 OD: 219.075 Avg 8.13 7.67 Remaining Life: Spec: ASME B31.3 **Comments:** ASSUMED NOMINAL **Retirement Date: CML Description** Flange ANSI: Material: SA-234-WPB Baseline 35 **PIPING** 2014 2019 CA Nominal T Min LTCR mm/yr Flag STCR mm/yr Shape: 90° Elbow Min 7.77 7.67 7.156 1.022 8.179 0.020 0.073 OD: 219.075 8.18 7.98 **Remaining Life:** Avg Spec: ASME B31.3 Comments: ASSUMED NOMINAL **Retirement Date:** 



**Comments:** 

**ASSUMED NOMINAL** 

Spec: ASME B31.3

# **Ultrasonic Corrosion Survey**

**Retirement Date:** 

	*All values are in millimet	ers unless otherwise	stated.				Survey Name:	Husky En	ergy	Date: JUNE 16 2019		
	Streamline Report #:	STL-19-0246-DM	IS 105							Inspector: DYLA	N SUNDQUIST	
LSD:	07-27-051-19W5	Area:	ANSELL				Location:	GAS PLAN	Т			
Jur #:	A0626024	Tag Number:	6619756	51			Vessel Name:					
CRN:	V9688.21	Year Built:	2012			Serial Number:	12-0779					
RT:	2	Vessel CA:	1.588 mm				Manufacturer:	CALHEX IN	IDUSTRIES			
		Shell MAWP:	2758	MAWT:	70		Tube MAWP:	2758	MAWT:	73	Pipe/Plate	
			KPA		°C			KPA		°C	0	
CML D	escription		Baseline				Flange ANSI:	;	Material:	SA-234-WPB		
40	PIPING		2014	2019		Flag	CA	Nominal	T Min	STCR mm/yr	LTCR mm/yr	
Shape:	90° Elbow	Min	8.00	8.64		7.156	1.022	8.179		0.000	0.000	
OD:	219.075	Avg	8.38	8.76						Remaining Life:		
Spec:	ASME B31.3	Comments:	ASSUME	D NOMIN	AL					Retirement Date:		
CML D	escription		Baseline				Flange ANSI:	<u> </u>	Material:	SA-234-WPB		
45	PIPING		2014	2019		Flag	CA	Nominal	T Min	STCR mm/yr	LTCR mm/yr	
Shape:	90° Elbow	Min	7.82	8.03		7.156	1.022	8.179		0.000	0.022	
OD:	219.075	Avg	8.26	8.13						Remaining Life:		

### ( COPPETTED

#### FORM U-1 MANUFACTURER'S DATA REPORT FOR PRESSURE VESSELS (2010)

As Required by the Provisions of the ASME Boiler and Pressure Vessel Code Rules, Section VIII, Division

	-		
n 1	A	626	024

1.	Manufactured and certified by CALHEX INDUSTRIES LTD. 9515 48 <sup>TH</sup> STREET S.E., CALGARY, ALBERTA, CANADA T2C 2R1																			
(Name and address of Manufacturer)																				
2.	Manufa	actured for			Husky Oil Operations Ltd. 707 – 8th Avenue S.W. Calgary, AB T2P 1H5															
					(Name and address of Purchaser)															
3.	Location of installation Husky Oil Ansell Gas Plant Edson, AB LSD# - 07-27-051-19-W5M																			
	(Name and address)																			
4.:	Туре			Horiz	ontal		_			Heat Ex	chang	er					12	-0779		
			(Horizo	ntal, ver	tical, or s	sphere)			(Tank, s	separator, jkt	vessel, h	eat exh.,etc.)				(Manuf	acture	r's serial nu	mber)	
-		V9688.21 12-0779-S Rev. 0 & T Rev. 0												2012						
5.	A C ME	(CR Code, Section	,				201	D <b>8. 201</b>	rawing No.)			2714	(Nation	al Board h	Number.)			(Y	ear Built)	
J	NOIVIL	Code, decilor	VIII, DIV. I			ſ	Edition and			**		(Code Case N	umber)		-	Specia	1 Servi	ce per UG-1	20(d)}	
Items	6-11	incl. to be cor	npleted for	sinale w	all vess	-				heat exchan	ers. or	chamber of mul		er vessel		•		•	. "	
		(a) Number of	-	-		,,,	2			Overall length				' <b>–</b> 8.75						
_				- 10							_	5								
		Course(	s)				Material		Thi	ckness	L	Long Joint (Cat A	<b>A</b> )	Circun	n Joint (Cat	A,B, &	C)	Heal	Treatment	
N	lo.	Diameter, in	Length (	t & in.)		Spec./	Grade or 1	уре	Nom.	Соп	Туре	Full,Spot,None	Eff.	Туре	Full,Spot,No	ne	Eff.	Temp.	Time	
	1	23"	39' – 8	.750"		S	A333-6		0.500"	0.0625"	S	None	1.0	7/1	Spot *	0	.70	:-		
	1	23"	8' -	0"		S	A333-6		0.500"	0.0625"	S	None	1.0	7/1	Spot *	0	.70	:=	6	
_													- "			_	-			
7.	Heads	: (a)										(b)								
		\ <del>-</del> /	-		(Mater	ial spec	number.	grade or t	type) (H.T time	e & temp.)		(5)		aterial spe	ec number, ç	grade o	r type	) (H.T time	& temp.)	
	T	nation (Ton	Thic	kness	Ė	Rad	ius	Elliptica	I Conica	1	Hemisr	oherical	Flat	Side	o Pressure			Category A	1	
		ocation (Top, ottom, Ends)	Min	Cor	m. C		(nuckle	Ratio	Apex An	10		dius	Diamet	er Conve	x Concave	Туре	Full.	Spot, None	Eff.	
(a)	T		,																	
(b)																				
-	lf remo	vable, bolts us	ed (describe	other fa	stenina)		-			•										
8.	Type o	f jacket								(Mate	-	number, grade, cket closure	size, nun	nber)						
0.	,,,,,,,	. journet									=			(Descr	ibe as ogee	and we	eld, ba	r, etc)		
	lf bar, (	give dimension	s													If bolte	d, des	cribe or ske	tch.	
9.	MAWP	-	400		15	psi —	at max. te	mp	163	163	°F	Min. design	metal ten	ip.	_49	°F	at	<b>400</b> pt	si.	
			(Internal)	(	External	)		(Ir	nternal)	(External)										
10.	Impact	test	No, exem	pt per	UCS-	66(a)(	c)(d)(g)	Fig. U	ICS-66 Note	e (c) & UC:	S-67(a	)2 at te	est tem	peratu	re of	°F				
					(Ir	ndicate	yes or no a	ind the co	omponent(s) imp	pact tested)										
11.	Hydro.	,pneu.,or comb	test pressu	re				520	) psi			Proof test					-			
		nd 13 to be co	mpleted for	_							-27									
12.	Tubest	neet:		SA510	5-70N		_ =		23"		1.	5625"	0.125"				Welded			
			[Station	nary (mai	terial spe	ec. no)]		[Diamete	r, (subject to pre	ess.)]	(Nomin	nal thickness)	(6	Corr. Allo	w:)	[/	Attachr	ment (welde	d or bolled)]	
_		- 2			-		· 196			<u> </u>				_		_				
	•	pating (materia	l spec. no.)				(Diamet	эг)	,	Nominal thickr	,		(Corr		_			(Attachmer		
13.	Tubes			SA17	79 **				0.750"			16 BWG	-	44	0		Straight			
			(Materia	spec. no	o, grade	or type	)		(O.D.)		(Non	ninal (hickness)		(Nurr	ber)			[Type (str	aight or U)]	
Items	14-18	3 incl. to be co	mpleted fo	r inner c	hamber	s of jac	keted ves	sels or cl	hannels of heat	t exchangers										
14.	Shell:	(a)No. of cour	se(s)				2		(b)	Overall length	(ft & in.)	):			2'	<b>– 10</b> '	,			
		Course(	s)			Mat	erial		Thickne	ess	1	Long Joint (Cat./	A)	Circur	n. Joint (Cat.	A.B. 8	(C)	Hes	t Treatment	
	_ 1				_						1						÷		Time	
-	0.	Diameter	Lengtl		Sp		de or Type	,	Nom.	Corr.	Туре	Full,Spot,None	Eff.	Type	Full,Spot,N		Eff.	Temp	Time	
	2	23"	1' - 5			SA3	33-6		0.500"	0.0625"	S	None	1.0	1/7	Spot		0.70		•	
					<u></u>						L	l				050	F0 1			
15.	Heads:	(a)							F2 CL.1			(b)				350-L				
r—								r, grade o	or type) (H.T T		1		r .			1	or typ		ne & Temp )	
		Location (To		Thicknes			Radius	_	Elliptical	Conical	He	emispherical	Flat		to Pressure	1	1_	Catego		
_		End	Mir		Corr.	Crowr	Knuck	le	Ratio	Apex Angle		Radius	Diamet	er Conv	ex Concav	е Туре	Full	,Spot,None	Eff	
-	a)	End	2.75	-	0625"	-	-	_					36" 36"	-	-	-	$\vdash$			
	o)	End	2.7	D.U.	0625"								36"				$\perp$			

If removable, bolts used (describe other fastening).

(24) 1.50" x 9.250" Lg. SA193-B7 UNC Studs / (48) 1.50" SA194-2H UNC Nuts (Material spec, number, grade, size, number)

					FORM U-1 (Bac	<u>k)</u>						
16. MAWP	400	1:	5 psiat	max temp 158	158	°F M	n design mel	al temp -49	°F at	4	<u>00   </u> Psi	
	(Interna	al) (Exte	rnal)	(Internal)	) (External)	_						
17. Impact test	7. Impact test No, exempt UCS-66(a)(c)(d)(g), Fig. UCS-66 Note (c) & UCS-67(a)2. at test temperature of °F.											
(Indicate yes or no and the component(s) impact tested)												
18. Hydro, pneu, or con	b test	press		520 psi		Proc	f test			_		
•				одо рол			9,					
19. Nozzies, inspection,	19. Nozzles, inspection, and safety valve openings:											
Purpose		Diameter	Flange		aterial		hickness	Reinforcement	Attachmer		Location	
(Inlet, Outlet, Drain, etc.) Shellside Inlet	No.	or Size 8" 300 CL	Type RFWN	Nozzle SA333-6	Flange SA350-LF2 CL.1	0.500"	0.0625"	Material SA516-70N	Nozzle UW16.1c	Flange BW	(Insp. Open.) Shell Top	
Shellside Outlet	1	8" 300 CL	RFWN	SA333-6	SA350-LF2 CL.1		0.0625"	SA516-70N	UW16.1c	BW	Shell Bottom	
Tubeside Inlet	1	8" 300 CL	RFWN	SA333-6	SA350-LF2 CL.1	0.500"		SA516-70N	UW16.1c	BW	Channel Bottom	
Tubeside Outlet	1	8" 300 CL	RFWN	SA333-6	SA350-LF2 CL.1	0.500"	0.0625"	SA516-70N	UW16.1c	BW	Channel Top	
T.I.	4	1"	CPLG	SA350-LF2 CL.1	1881	6000 CL	0.0625"	5	UW16.1a		Inlets/Outlets	
P.I.	4	3/4"	CPLG	SA350-LF2 CL.1		6000 CL		=	UW16.1a	ě.	Inlets/Outlets	
Vent	1	1"	CPLG	SA350-LF2 CL.1	(4)	6000 CL		¥	UW16.1a	-	Channel Top	
Drain	1	1"	CPLG	SA350-LF2 CL.1	72:	6000 CL	0.0625"		UW16.1a		Channel Bottom	
	+-											
20 0 0 0 0 0 0 0		No.		1	On 6 and all 2		<u></u>	ا ۱۸۵مامام	to Shell &	Chan	I Covers	
20. Supports:	Skirt		4	Legs n/a	Other Saddles		med	weided			iei Covers	
		(Yes/no)	(Number)	(Number)	(Describe	•			(Where a	na now)		
				•	I Inspectors have been furr	iisnea for the	tollowing item	is of the report:				
(list the name of part,	item n	umber, Manufactui	rer's name an	d identifying number):								
22. Remarks:	(2) 2	24" 300 CL RFW	/N Channel	Flanges – SA350-LF	<sup>2</sup> 2 CL.1							
SAFETY VALVES:		P.S.V. on	pipina pe	r UG-125 (a) to be	installed by owner	· c	UBIC CAPAC	ITY: 123.0	)4 cu. ft.			
		-		(3) (0 10		_		:				
SURFACE AREA:		4146.9 sq										
SERVICE:	Inle	t Gas Heat Ex	cchanger								gth – 48' – 0" Lg.	
ITEM #:	E-1	02B				Con	structed t	o Drawing #	12-0779–S	Rev. 1	& T Rev. 0.	
					ICATE OF SHOP C							
· ·					ign, material, construction,	and workman	ship of this ve	essel conform to th	ie			
ASME BOILER AND PF U Certificate of Authori			z, Section VIII	33238	Expires	Δr	ril 22	.20 14	10	1		
			-	00200			111 22	14	-1/d		9	
Date OCT 0	7 21	<b>]]</b> Name		Calhex Indus	stries Ltd.	Sig	ned		- C			
			-	(Manufac	turer)	_	-	I.(	(Re	resentati	ve)	
				CERTII	FICATE OF SHOP II	NSPECTIO	N					
I, the undersigned, hold	ing a v	alid commission is:	sued by the N	ational Board of Boiler a	nd Pressure Vessel Inspec	tors and/or th	e State or Pro	ovince of ALBE	RTA			
and employed by		-		ABSA		11		B, CANADA			have inspected	
the pressure vessel des			•		ecember 14			that, to the best of				
		•			AND PRESSURE VESSEL						,	
				• •	escribed in this Manufactur	•	on; Funnerm	ore, neither the in	spector nor nis	s/ner empi	loyer shall be liable	
in any manner for any p	ersona	i injury or property	uamaye or a	loss of arry kind arising t	om or connected with this	Inshection		AF	. 4 4E NIE	100-		
Date OCT	03	2013 Signed		12	11.		Commission	s At	145 NE	3 1237	75 A, B, N	
		1.0 10	*	(Authorize	ed Inspector)				rd (incl.endors	ements).S	State, Province, and number]	
					OF FIELD ASSEM							
	ments	on this report are o	correct and the	at the field assembly con	struction of all parts of this	vessel confo	ms with the r	equirements of AS	ME BOILER A	AND PRES	SSURE VESSEL CODE,	
Section VIII, Division 1.												
U Certificate of Authoria	zation I	Number			Expires	-	, 20	<del>_</del> :				
Date		Name				Sia	ned				ï	
-				(Assemb	oler)		8		(Re	presentati	ve)	
				CERTIFICAT	E OF FIELD ASSEM	BLY INSF	ECTION					
I, the undersigned, I	olding	a valid commission	n issued by th		er and Pressure Vessel Ins			Province of				
and employed by							of					
have compared the	stateme	ents in this Manufa	cturer's Data	Report with the describe	d pressure vessel and stat	e that parts re	eferred to as o	data items				
have compared the statements in this Manufacturer's Data Report with the described pressure vessel and state that parts referred to as data items  not included in the certificate of shop inspection, have been inspected by me and to the best of my knowledge and belief, the Manufacturer has constructed and assembled this pressure vessel												
in accordance with ASME BOILER AND PRESSURE VESSEL CODE, Section VIII, Division 1. The described vessel was inspected and subjected to a hydrostatic test of												
signing this certifica	e neith	ner the Inspector no	or his/her emp	oloyer makes any warran	ty, expressed or implied, co	oncerning the	pressure ves	sel described in th	nis Manufactur	er's Data	Report	
Furthermore, neither	the In	spector nor his/her	employer sha	all be liable in any manno	er for any personal injury o	r property dar	nage or a los	s of any kind arisir	ng from or con	nected wit	h this inspection	
Date		Signed	-		Commi	_						
			(Aut	horized Inspector)			(National Boa	ard (incl. endorsem	ients), State, F	Province a	nd number.)	