

Certificate/Serial/Job No:

AC75 / 18

Quality Department: *Joe Marcia*

Quantity	Size (NPS)	Class	Product	Description	Type	SONumber	Line	Sold to	Date
24	2	600	/ 103026	DSI 165XU	SWING				3/8/2014

Pressure Test: API598	☒ Satisfactory	Shell Pressure : 2225 psi 15340.8 kPa	BackSeat : psi kPa	Seat Pressure 1650 psi 11376.35 kPa	Seat Air Pressure psi kPa
------------------------------	--	--	-----------------------	--	------------------------------

Part	Specif.	HEAT No	Chemical Composition [%]													Mechanical Properties										
			C	Si	Mn	P	S	Ni	Cr	Mo	Cu	V	Nb	Al	N	Tensile [ksi] [MPa]	Yield [ksi] [MPa]	Elong [%]	Redu [%]	Hard [HB]	Ch.1 [J]	Ch.2 [J]	Ch.3 [J]	Ch. A [J]	Temp. [F] [C]	HT
BODY	ASTM A216 WCB-2008	VA 1825	0.215	0.453	0.864	0.025	0.011	0.045	0.148	0.007	0.028	0.003		0.050	75.40 519.86	47.85 329.9	32.5	62	154							N
CLAPPER	ASTM A105-2005	. 10731	0.18	0.18	0.94	0.025	0.014	0.03	0.09	0.003	0.04	0.002			73.95 509.87	50.03 344.9	32.5	67	154							N
COVER	ASTM A105-2005	. 10879	0.20	0.19	0.93	0.022	0.012	0.02	0.08	0.002	0.04	0.002			78.30 539.86	51.48 354.9	33	65	161							N

Heat Treatment Codes:

A : Annealing	AC : Air Cooling	DA : Double Aged	FT : Furnace Treatment	N : Normalizing	OQ : OilQuenched
Ph-3: Precipitation Hardening	SA : Solution Annealed	SQ : Solution Quenched	ST : Solution Treatment	T : Tempering	WC : Water Cooling
WO : Water Quenched	WT : Water Quenched/ Tempered			NT : Normalized/Tempered	

Part	Material
BODY	ASTM A216 WCB
BOLTING	ASTM A193 B7 / ASTM A194 2H
COVER	ASTM A105
DISC-WEDGE-CLAPPER	ASTM A105 +13%Cr Overlay
HINGE PIN	ASTM A276 410
SEAT RING	ASTM A105 + Stl.6 Faced

Valves Tested per API598


We hereby certify, that the material described above complies with the order requirements.

EC Declaration of Conformity: JEV (Jiangyin Eastern Valve Co. Ltd.), Jiangsu Province, 214423, P.R. China

According to Annex VII of Pressure Equipment Directive 97/23/EC, hereby declare that the products detailed above are in compliance with PED 97/23/EC and have been manufactured in accordance with conformity assessment module B+D as approved Det Norske Veritas Inspection AB as Identification No 0575 (formally 0409). The products may cover Category I, II and III of pressure equipment. For the most specific risks of this equipment, safety and compliance with essential requirements of the Directive has been based on API 600, API598, ASME B16.34, ASME B16.5, ASME B16.10 latest edition.

Undersigned by Liu Jian Qing, representing Jianyin Eastern Valve company Ltd. :

刘建清



Inspection Certificate and Material Test Report (EN10204-1991 3.1.B / EN10204-2004 3.1)

DSI Valve Solutions
12735 Dairy Ashford
Stafford TX 77477
281-637-2000 - Fax 281-637-2299
www.dsiValve.com

Certificate/Serial/Job No:

ACT5 / 18

Quality Department: *Glenn Mace*

Quantity	Size (NPS)	Class	Product	Description	Type	SO Number	Line	Sold to	Date
24	2	600	/	103026	DSI 165XU	SWING			3/8/2014
Pressure Test: API598 ☒ Satisfactory					2225 psi	BackSeat:	psi	Seat Pressure	psi
					15340.8 kPa		kPa	11376.35 kPa	Seat Air Pressure

Part	Specif.	HEAT No	Chemical Composition [%]													Mechanical Properties									
			C	Si	Mn	P	S	Ni	Cr	Mo	Cu	V	Nb	Al	N	Tensile Yield	Elong	Redu	Hard	Ch.1	Ch.2	Ch.3	Ch.4	Temp.	HT
																[ksi]	[ksi]	[%]	[%]	[HRC]	[H]	[H]	[H]	[H]	[H]
																[MPa]	[MPa]	[%]	[%]	[HRC]	[H]	[H]	[H]	[H]	[H]