

Husky Energy		Non Pressure Storage		Husky Purchase Order No. P.O. 8400899432	
Data Collected By: <u>Ryan Rirao</u>		Entry Date: <u>24-Mar-15</u>		<u>1000016442</u>	
Equipment Class	<input type="checkbox"/> Bin <input type="checkbox"/> Silo	<input type="checkbox"/> Gas Boot <input type="checkbox"/> Sump	<input type="checkbox"/> Pond <input checked="" type="checkbox"/> Tank	P&ID #:	
Equipment Description: <u>100BBL skidded tank</u>				Exist. Equip. ID:	<u>13663</u>
Unit Yard	<u>ea</u>	Acquis Value \$	<u>\$13,115.00</u>	Acquis Date	<u>2015</u>
Equipment Status:	<input type="checkbox"/> In-Service Fully Utilized <input type="checkbox"/> In Service Under-utilized <input type="checkbox"/> Idle <input type="checkbox"/> Scrap <input type="checkbox"/> Field Idle				
Ownership Status:	<input type="checkbox"/> Leased <input type="checkbox"/> Rented <input checked="" type="checkbox"/> Owned				
Manufacturer:	<u>Argo Sales</u>		Year Built:	<u>2015</u>	
Equipment Condition:	<u>new</u>	Model No.:	<u>100 BBL</u>		
Construction:	<input checked="" type="checkbox"/> Skidded <input type="checkbox"/> Packaged <input type="checkbox"/> Housed <input type="checkbox"/> Packaged Portable <input type="checkbox"/> Packaged Stationary				
Skid Weight:	<u>153/338</u> Kg / Lbs	Skid Size:	<u>W 96"</u> x <u>L 126"</u> x <u>H 6"</u> m / ft		
Common Characteristics					
Fluid Description:	Service: <input checked="" type="checkbox"/> Sweet <input type="checkbox"/> Sour		Volume:	<u>16 m3</u>	m3 / ft3
MAWP:	<u>16 oz.</u> kPag / psig / oz	@ Max. Temp:	<u>80 C</u> °C / °F	MDMT:	<u>-29C</u> °C / °F
Diameter:	<u>2896/ 114</u> mm / in	Length/Height (S/S):	<u>2.438/ 8</u> m / ft	Depth:	<u>2.438/ 8</u> m / ft
Shell Mat'l:	<u>A36</u>	Shell Thickness:	<u>4.8/ 3/16"</u> mm / in	Shell C.A.:	<u>0</u> mm / in
Floor Mat'l:	<u>A36</u>	Floor Thickness:	<u>6.4/ 1/4"</u> mm / in	Floor C.A.:	<u>0</u> mm / in
Roof Mat'l:	<u>A36</u>	Roof Thickness:	<u>4.8/ 3/16"</u> mm / in	Roof C.A.:	<u>0</u> mm / in
Nozzle Mat'l:	<u>A105/A106</u>	Nozzle Thickness:	<u>Sch. 40</u> mm / in	Nozzle Rating:	<u>150</u> Ansi
Insulated:	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Insulation Type	<u>None</u>	Insulation Thick.:	<u>NIL</u> mm / in
# Manways:	<u>1</u>	# of Inspection Ports:	<u>1</u>	Painted / Primed:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Secondary Containment Type:	<input type="checkbox"/> Earthen Clay <input type="checkbox"/> Imperious Synthetic Material <input type="checkbox"/> Double Wall <input checked="" type="checkbox"/> Other				
Internals:					
Component Types:	<u>N/A</u>	Component Man.	<u>N/A</u>	Component Model:	<u>N/A</u>
Component Removable:	<input type="checkbox"/> Yes <input type="checkbox"/> No	Component C.A.:	<u>N/A</u>	mm / in	
Internal Coating:	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Int. Coating / Cladding Type:	<u>NIL</u>		
Additional Characteristics for Tank					
Tank Type:	<input type="checkbox"/> Underground <input checked="" type="checkbox"/> Surface	# Of Walls:	<input checked="" type="checkbox"/> single <input type="checkbox"/> Double		
Design Standard:	<input type="checkbox"/> API 650 <input type="checkbox"/> API 620 <input checked="" type="checkbox"/> API 12F <input checked="" type="checkbox"/> Other Mod.				
Fabrication Type:	<input checked="" type="checkbox"/> Shop <input type="checkbox"/> Field				
Pressure Protection:	<input checked="" type="checkbox"/> Vent <input checked="" type="checkbox"/> Thief Hatch Vacuum Breaker Manufacturer: <u>N/A</u> <input type="checkbox"/> Vacuum Breaker Vacuum Breaker Model: <u>N/A</u>				
Fire Tubes Exists:	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Vacuum Breaker Service Date: <u>N/A</u>				
# of Firetube:	<u>N/A</u>	Firetube S/N:	<u>N/A</u>	Firetube Rating:	<u>N/A</u> Btu/hr
Desand Type:	<u>N/A</u>	Desand Connection:	<u>N/A</u> mm / in	Truck Connection:	<u>N/A</u> mm / in
Enviro Vault:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Burner Manufacturer:	<u>N/A</u>		
Sacrificial Anodes:	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	# of Sacrificial Anodes:			
Additional Characteristics for Gas Boot					
Prov.Reg. No.:		CRN#			
Head Mat'l:		Head Thickness:	<u> </u> mm / in	Head C.A.:	<u> </u> mm / in
Additional Characteristics for Pond, Silo					
Volume:	<u> </u> m³	Liner:	<input type="checkbox"/> Yes <input type="checkbox"/> No	Liner Material:	<u> </u>
Fluid Description:	Service: <input type="checkbox"/> Sweet <input type="checkbox"/> Sour				
Diameter:	<u> </u> m	Depth:	<u> </u> mm		
Design Min Temp:	<u> </u> °C	Design Max Temp:	<u> </u> °C		
Capacity:	<u> </u> tonne				
Comments					
Material Transfer Information					
Transfer Recorded by:		Date			
From	LSD <u> </u> Sec <u> </u> Twp <u> </u> Rge <u> </u> W/ <u> </u>				
Transfer Yard					
To	LSD <u> </u> Sec <u> </u> Twp <u> </u> Rge <u> </u> W/ <u> </u>				
Facility					
Receiving AFE: <u> </u>					