

Bitumen Washing Machine

For the removal of bitumen residues and small parts and glassware with non-flammable solvents trichloroethylene (TRI), perchloroethylene (PER, Tetra) or methylene chloride (methylene) in a closed cycle.

- ▶ Heated washing area approx. 500 x 300 x 300 mm with spray nozzles for internal and external cleaning of up to 8 parts
- ▶ Collecting sieve at the solvent drain for coarse soiling
- ▶ Integrated distillation at the solvent tank and residue tank
- ▶ Integrated recirculating air drying at the end of the process
- ▶ Variable process control via integrated SPS with variable cleaning and drying times
- ▶ Connections for solvent supply and disposal
- ▶ Various insert racks optionally available

Technical data

Dimensions	1030 x 780 x 1280 mm
Weight	196 kg
Electrical data	3/N/PE, 400 V, 50 Hz, 4kW
Producer	infraTest Prüftechnik (DE)
Customs Tariff Number	84222000

20-5010

20-5010-60

Bitumen Washing Machine 60 Hz

Advantage:

- ▶ Closed solvent cycle
- ▶ Different accessories possible
- ▶ Easy programming and operation
- ▶ Increased efficiency of the workflow through an uncomplicated and quick purification



Insert basket for small parts

20-5010E10

ACCESSORIES