

MERCER VALVE INSPECTION AND TEST REPORT

BRANCH: Red Deer

Serial #: 469430

Work Order: 76413

Customer PO#: 53995

Date:

A#:

10/8/2008

Facility:

Cust. Ref.:

HALKIRK

LSD:

Customer: PAINTEARTH ENERGY SERVICES INC.

PSV Location:

Cust Id:

Valve PO: 53995

VALVE DATA

Man.:

Mercer

Model: 91-17D51V07E1

Orifice: D

Serial: 469430

Conn:

Threaded

Inlet: 1 inch MNPT

Temp:

Outlet: 1 inch FNPT Cold/Diff Set Press: PSI

Cap: 329 SCFM

Set Pres: Lift Lever:

150 PSI

Back Press: PSI Cap Assembly: Closed

Trim: Standard

Code Symbol: UV

CRN#: 0G8841.5C

CUSTOMER INSTRUCTIONS

Valve Instruct. Factory Set

Instructions:

Sold New Valve

Reset Required?

RESET INFORMATION: New Pressure:

New Cold/Diff Set:

New Capacity:

COMPONENTS INSPECTION

Components Installed

Components Removed

New Model #:

Spring #:

Valve Medium:

New Inlet Size:

Trim:

BPM

Temperature:

Disassembly:

Inspection:

Leakage:

Murray Greer

Reassembly:

FINAL TEST:

Test Medium:

Simmer:

Set Pressure:

B.P. Test:

Cold/Diff Set:

Test Gauge:

Tested by:

Reseat:

FINAL INSPECTION:

End Protectors Installed: Painted: Ship Container:

Palletized:

Flex Gaskets Supplied:

Final Inspection: Murray Greer

SEAL Installed:

Customer Inspection

INSPECTION ID#:

7922

OF-087

Comments:



MERCER VALVE INSPECTION AND TEST REPORT

BRANCH: Red Deer

Serial #: 448324

Work Order: 76449

Customer PO#: 54063

Date:

A#:

10/20/2008

Facility:

HALKIRK

LSD:

Customer: PAINTEARTH ENERGY SERVICES INC.

PSV Location: Cust Id:

Valve PO: 54063

0805-44

VALVE DATA

Man.:

Cust. Ref.:

Mercer

Model: 91-17D51T14E1

Inlet: 1 inch MNPT

Orifice: D

Serial: 448324 Outlet: 1 inch FNPT

Conn: 1440 PSI Set Pres:

Threaded

Back Press: PSI

Temp:

Cold/Diff Set Press: PSI

Cap: 2925 SCFM

Lift Lever:

Cap Assembly: Closed

Trim: Standard

Code Symbol: UV

CRN#: 0G8841.5C

CUSTOMER INSTRUCTIONS

Valve Instruct. Modify

Instructions:

Convert to AB Sour

Reset Required?

RESET INFORMATION: New Pressure:

1330 PSI

New Cold/Diff Set:

New Capacity: 2705 SCFM

COMPONENTS INSPECTION

Components installed

05-014 AL SPRING RED CAP

UVL RESET TAG

Components Removed

05-014 SPRING

SILVER CAP

New Model #: . 91-17D51T14E1S

Spring #:

05-014 AL

New Inlet Size:

Trim:

Standard

Temperature:

Disassembly: Murray Green

Valve Medium: Inspection:

Gas / Air Murray Green

Reassembly:

Murray Green

FINAL TEST:

Test Medium: Reseat:

Air

1048 PSI

1328 PSI Simmer: Leakage: 0 BPM

Set Pressure: 1330 PSI B.P. Test:

60 PSI

Cold/Diff Set:

PSI

Test Gauge:

RD-1/14

Tested by:

Jeff Durbak

FINAL INSPECTION:

SEAL Installed:

End Protectors Installed: 🔽

Painted:

Palletized:

Ship Container: 🗹

Flex Gaskets Supplied:

Final Inspection: Murray Green

Customer Inspection

INSPECTION ID#:

7967

Comments:





CALIBRATION REPORT

	COD DAMEE ADTI	F-11-5-01	DOMOGRADA MINICIPAL	A D
PREPARED	FOR PAINTEARTH	ENERGY	BOX 24 HALKIRK, A	48

INSTRUMENT INFORMATION

MANUFACTURER: SWAGELOK	MODEL NUMBER: SS-4R3A5-BU
IDENTIFICATION NUMBER: PES-893	ACCURACY: N/A
JOB: 54136	RANGE 750-1500 PSI
TARPON NUMBER: TARED-P-2247	TYPE: PSV
CALIBRATION DATE: 22-Oct-08	CALIBRATION DUE: 22-Oct-09

CALIBRATION DATA

CRACK SET POINT	ACTUAL	FOUND	LEFT
0	0	0	0
N/A	N/A	N/A	N/A
1330 PSI	1330 PSI	N/A	1330 PSI
	'Se ** **.		

TEST EQUIPMENT USED

SERIAL NO.	MAKE	MODEL NO.	CALIBRATION DATE
404643	CRYSTAL	5KPSIXP21	18-OCT-07

COMMENTS: The instrument was calibrated against laboratory standards that are either traceable to the National Institute of Standards and Technology, (NIST), National Research Council, (NRC), or are derived by approved ratio techniques.

CALIBRATION TECHNICIAN: Alain Pedneault

OUT 23 2009

21 m



CALIBRATION REPORT

INSTRUMENT INFORMATION

MANUFACTURER: SWAGELOK	MODEL NUMBER: SS-4R3A5-BU
IDENTIFICATION NUMBER: PES-869	ACCURACY: N/A
JOB: 54064	RANGE 1500-2250 PSI
TARPON NUMBER: TARED-P-2223	TYPE: PSV
CALIBRATION DATE: 14-Oct-08	CALIBRATION DUE: 14-Oct-09

CALIBRATION DATA

ACTUAL	FOUND	LEFT
0	0	0
N/A	N/A	N/A
2030 PSI	N/A	2030 PSI
	0 N/A	0 0 N/A N/A

TEST EQUIPMENT USED

SERIAL NO.	MAKE	MODEL NO.	CALIBRATION DATE
404643	CRYSTAL	5KPSIXP21	18-OCT-07

COMMENTS: The instrument was calibrated against laboratory standards that are either traceable to the National Institute of Standards and Technology, (NIST), National Research Council, (NRC), or are derived by approved ratio techniques.

CALIBRATION TECHNICIAN: Alain Pedneault



CALIBRATION REPORT

DDEDADED		AITEADTII	EMEDOVIDO	NO A LIALIZIDIZ	ΛD
PREPARED	FUR PA	NIEARIA	ENERGYBU	DX 24 HALKIRK, .	AD

INSTRUMENT INFORMATION

	·
MANUFACTURER: SWAGELOK	MODEL NUMBER: SS-4R3A5-BU
IDENTIFICATION NUMBER: PES-870	ACCURACY: N/A
JOB: 54064	RANGE 750-1500 PSI
TARPON NUMBER: TARED-P-2224	TYPE: PSV
CALIBRATION DATE: 14-Oct-08	CALIBRATION DUE: 14-Oct-09

CALIBRATION DATA

CRACK SET POINT	ACTUAL	FOUND	LEFT
0	0	0	0
N/A	N/A	N/A	N/A
1330 PSI	1330 PSI	N/A	1330 PSI

TEST EQUIPMENT USED

SERIAL NO.	MAKE	MODEL NO.	CALIBRATION DATE
404643	CRYSTAL	5KPSIXP21	18-OCT-07

COMMENTS: The instrument was calibrated against laboratory standards that are either traceable to the National Institute of Standards and Technology, (NIST), National Research Council, (NRC), or are derived by approved ratio techniques.

CALIBRATION TECHNICIAN: Alain Pedneault